




List 14001

NRT, Plug (4P-4.5P), Bottom (2P-2.5P), Short Bottom (1P-1.5P)



HSS-Co	TIN	S/O	BR
--------	-----	-----	----



Units: Inch

Tap Size	Lead	Thread Limit	EDP Number	Coating Suffix			Overall Length L	Thread Length Lc	Neck Length Ln	Shank Dia. d	Square Width k	Square Length lk	Tap Drill Size		Class of Fit	
				Bright	S/O	TiN							Min	Max	2B	3B
0 - 80 UNF	1.5P	H2	14001000	00	01	05	1.625	0.311	0.350				0.0536	0.0549		
		H3	14001001	00	01	05										
		H2	14001002	00	01	05										
	2.5P	H3	14001003	00	01	05										
		H4	14001004	00	01	05										
		H5	14001005	00	01	05										
		H6	14001006	00	01	-										
1 - 64 UNC	2.5P	H7	14001007	00	01	-										
		H2	14001008	00	01	05										
		H3	14001009	00	01	05										
		H4	14001010	00	01	05										
		H5	14001011	00	01	05										
1 - 72 UNF	1.5P	H6	14001012	00	01	-	1.688	0.374	0.413	0.141	0.110	0.188	0.0659	0.0673	H3	H2
		H2	14001014	00	01	05										
		H3	14001015	00	01	05										
	2.5P	H2	14001016	00	01	05										
		H3	14001017	00	01	05										
		H4	14001018	00	01	05										
		H5	14001019	00	01	05										
2 - 56 UNC	1.5P	H6	14001020	00	01	05	1.750	0.437	0.476				0.0769	0.0787		
		H7	14001021	00	01	-										
		H2	14001022	00	01	05										
	2.5P	H3	14001023	00	01	05										
		H4	14001024	00	01	05										
		H2	14001025	00	01	05										
		H3	14001026	00	01	05										
		H4	14001027	00	01	05										
		H5	14001028	00	01	05										
2 - 64 UNF	2.5P	H6	14001029	00	01	05							0.0780	0.0796		
		H7	14001030	00	01	05										
		H8	14001578	00	-	-										
		H9	14001579	00	-	-										
		H2	14001031	00	01	05										
		H3	14001032	00	01	05										
		H4	14001033	00	01	05										

Packed: 1 pc.
EDP's listed above are stocked standard, other coatings available upon request.
Specify treatment at time of order.

continued on next page

List No.	Work Material																
	P					M			K	N		S	H				
	Carbon Steels			Alloy Steels	Die Steels	Stainless Steels			Cast Iron	Aluminum		Nickel Alloy	Titanium	Hardened Steels			
	Low	Med.	High			300	400	17-4 PH		6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
14001	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>			<input type="checkbox"/>				
SFM	35-100	20-50	15-25	15-25	15-20	15-40	15-40	10-25		50-90	45-100			10-15			

good best





HY-PRO® NRT

Premium Design for a Wide Range of Materials

List 14001 (Continued)




HSS-Co

TiN

S/O

BR

NRT, Plug (4P-4.5P), Bottom (2P-2.5P), Short Bottom (1P-1.5P)



Units: Inch

Tap Size	Lead	Thread Limit	EDP Number	Coating Suffix			Overall Length L	Thread Length Lc	Neck Length Ln	Shank Dia. d	Square Width k	Square Length lk	Tap Drill Size		Class of Fit	
				Bright	S/O	TiN							Min	Max	2B	3B
3 - 48 UNC	2.5P	H2	14001037	00	01	05	1.813	0.496	0.535				0.0884	0.0905		
		H3	14001038	00	01	05										
		H4	14001039	00	01	05										
		H5	14001040	00	01	-										
		H6	14001041	00	01	-										
		H7	14001042	00	01	-										
3 - 56 UNF	2.5P	H2	14001043	00	01	05	1.813	0.496	0.535				0.0899	0.0917	H3	H2
		H3	14001044	00	01	05										
		H4	14001045	00	01	05										
		H5	14001046	00	01	05										
		H6	14001047	00	01	05										
		H7	14001048	00	01	-										
4 - 40 UNC	1.5P	H3	14001049	00	01	05	1.875	0.295	0.559	0.141	0.110	0.188	0.0993	0.1018		
		H4	14001050	00	01	05										
		H5	14001051	00	01	05										
		H6	14001573	00	01	05										
		H7	14001574	00	01	05										
		H2	14001052	00	01	05										
	2.5P	H3	14001053	00	01	05										
		H4	14001054	00	01	05										
		H5	14001055	00	01	05										
		H6	14001056	00	01	05										
		H7	14001057	00	01	05										
		H8	14001580	00	-	-										
		H9	14001581	00	-	-										
		H10	14001582	00	-	-										
4.5P	H2	14001058	00	01	05											
	H3	14001059	00	01	05											
	H4	14001060	00	01	05											
	H5	14001061	00	01	05											
	H6	14001062	00	01	05											
	H7	14001063	00	01	05											
4 - 48 UNF	2.5P	H2	14001064	00	01	05	1.875	0.295	0.559	0.141	0.110	0.188	0.1014	0.1035		
		H3	14001065	00	01	05										
		H4	14001066	00	01	05										
		H5	14001067	00	01	05										
	4.5P	H6	14001068	00	01	-										
		H7	14001069	00	01	-										
		H2	14001070	00	01	05										
5 - 40 UNC	2.5P	H3	14001071	00	01	05	1.938	0.299	0.626				0.1123	0.1148		
		H4	14001072	00	01	-										
		H5	14001073	00	01	-										
		H6	14001074	00	01	-										
		H7	14001075	00	01	-										
		H2	14001076	00	01	-										

Packed: 1 pc.
EDP's listed above are stocked standard, other coatings available upon request.
Specify treatment at time of order.





List 14001 (Continued)



HSS-Co	TiN	S/O	BR
--------	-----	-----	----

NRT, Plug (4P-4.5P), Bottom (2P-2.5P), Short Bottom (1P-1.5P)

Units: Inch

Tap Size	Lead	Thread Limit	EDP Number	Coating Suffix			Overall Length L	Thread Length Lc	Neck Length Ln	Shank Dia. d	Square Width k	Square Length lk	Tap Drill Size		Class of Fit	
				Bright	S/O	TiN							Min	Max	2B	3B
5 - 40 UNC	2.5P	H7	14001081	00	01	05	1.938	0.299	0.626	0.141	0.110	0.188	0.1123	0.1148	H5	H3
		H2	14001082	00	01	05										
		H3	14001083	00	01	05										
	4.5P	H4	14001084	00	01	05										
		H5	14001085	00	01	05										
		H6	14001086	00	01	05										
		H7	14001087	00	01	05										
5 - 44 UNF	2.5P	H2	14001088	00	01	05										
		H3	14001089	00	01	05										
		H4	14001090	00	01	05										
		H5	14001091	00	01	05										
		H6	14001092	00	01	05										
		H7	14001093	00	01	05										
		4.5P	H2	14001094	00	01							05			
	H3		14001095	00	01	05										
	H4		14001096	00	01	05										
	H5		14001097	00	01	05										
	H6		14001098	00	01	05										
	H7		14001099	00	01	05										
	6 - 32 UNC		1.5P	H3	14001100	00	01	05								
		H4		14001101	00	01	05									
H5		14001102		00	01	05										
H6		14001575		00	01	-										
H7		14001576		00	01	-										
H8		14001577		00	01	-										
2.5P		H2		14001103	00	01	05									
		H3	14001104	00	01	05										
		H4	14001105	00	01	05										
		H5	14001106	00	01	05										
		H6	14001107	00	01	05										
		H7	14001108	00	01	05										
		H8	14001109	00	01	05										
		H9	14001110	00	01	05										
		H10	14001111	00	01	05										
		H11	14001583	00	-	-										
		H12	14001584	00	-	-										
		H14	14001599	00	-	-										
		4.5P	H2	14001112	00	01	05									
			H3	14001113	00	01	05									
H4			14001114	00	01	05										
H5	14001115		00	01	05											
H6	14001116		00	01	05											
H7	14001117		00	01	05											
H8	14001118		00	01	05											
H9	14001119		00	01	05											

Packed: 1 pc.
EDP's listed above are stocked standard, other coatings available upon request.
Specify treatment at time of order.

continued on next page

List No.	Work Material																
	P					M			K	N		S	H				
	Carbon Steels			Alloy Steels	Die Steels	Stainless Steels			Cast Iron	Aluminum		Nickel Alloy	Titanium	Hardened Steels			
	Low	Med.	High			300	400	17-4 PH		6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
14001	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>			<input type="checkbox"/>				
SFM	35-100	20-50	15-25	15-25	15-20	15-40	15-40	10-25		50-90	45-100			10-15			

good best





HY-PRO[®] NRT

Premium Design for a Wide Range of Materials

List 14001 (Continued)




HSS-Co

TiN

S/O

BR

NRT, Plug (4P-4.5P), Bottom (2P-2.5P), Short Bottom (1P-1.5P)



Units: Inch

Tap Size	Lead	Thread Limit	EDP Number	Coating Suffix			Overall Length L	Thread Length Lc	Neck Length Ln	Shank Dia. d	Square Width k	Square Length lk	Tap Drill Size		Class of Fit	
				Bright	S/O	TiN							Min	Max	2B	3B
6 - 32 UNC	4.5P	H10	14001120	00	01	05	2.000	0.370	0.685	0.141	0.110	0.188	0.1221	0.1253		
		H2	14001121	00	01	05										
		H3	14001122	00	01	05										
		H4	14001123	00	01	05										
		H5	14001124	00	01	05										
		H6	14001125	00	01	05										
		H7	14001126	00	01	05										
		H8	14001127	00	01	05										
		H9	14001128	00	01	05										
		H10	14001129	00	01	05										
	6 - 40 UNF	2.5P	H2	14001130	00	01							05			
			H3	14001131	00	01							05			
			H4	14001132	00	01							05			
			H5	14001133	00	01							05			
			H6	14001134	00	01							05			
		4.5P	H7	14001135	00	01							05			
			H8	14001136	00	01							05			
			H9	14001137	00	01							05			
			H10	14001138	00	01							05			
			H3	14001139	00	01							05			
8 - 32 UNC	1.5P	H4	14001140	00	01	05										
		H5	14001141	00	01	05										
		H2	14001142	00	01	05										
		H3	14001143	00	01	05										
		H4	14001144	00	01	05										
	2.5P	H5	14001145	00	01	05										
		H6	14001146	00	01	05										
		H7	14001147	00	01	05										
		H8	14001148	00	01	05										
		H9	14001149	00	01	05										
		H10	14001150	00	01	05										
		H11	14001585	00	-	-										
		H12	14001586	00	-	-										
		H14	14001600	00	-	-										
	4.5P	H2	14001151	00	01	05										
		H3	14001152	00	01	05										
		H4	14001153	00	01	05										
		H5	14001154	00	01	05										
		H6	14001155	00	01	05										
		H7	14001156	00	01	05										
H8		14001157	00	01	05											
H9		14001158	00	01	05											
H10		14001159	00	01	05											
8 - 36 UNF		2.5P	H2	14001160	00	01	05									
	H3		14001161	00	01	05										
	H4		14001162	00	01	05										
	H5		14001163	00	01	05										
	H6		14001164	00	01	05										
	H7		14001165	00	01	05										
	H8		14001166	00	01	05										
														0.1498	0.1527	

Packed: 1 pc.
EDP's listed above are stocked standard, other coatings available upon request.
Specify treatment at time of order.





List 14001 (Continued)



HSS-Co	TiN	S/O	BR
--------	-----	-----	----

NRT, Plug (4P-4.5P), Bottom (2P-2.5P), Short Bottom (1P-1.5P)

Units: Inch

Tap Size	Lead	Thread Limit	EDP Number	Coating Suffix			Overall Length L	Thread Length Lc	Neck Length Ln	Shank Dia. d	Square Width k	Square Length lk	Tap Drill Size		Class of Fit	
				Bright	S/O	TiN							Min	Max	2B	3B
8 - 36 UNF	2.5P	H9	14001167	00	01	05	2.125	0.374	0.752	0.168	0.131		0.1498	0.1527	H5	H3
		H10	14001168	00	01	05										
	4.5P	H2	14001169	00	01	05										
		H3	14001170	00	01	05										
		H4	14001171	00	01	05										
		H5	14001172	00	01	05										
		H6	14001173	00	01	05										
		H7	14001174	00	01	05										
		H8	14001175	00	01	05										
		H9	14001176	00	01	05										
H10	14001177	00	01	05												
10 - 24 UNC	1.5P	H3	14001178	00	01	05	2.375	0.492	0.866	0.194	0.152	0.250	0.1688	0.1730	H6	H4
		H4	14001179	00	01	05										
		H5	14001180	00	01	05										
		H6	14001571	00	01	05										
	2.5P	H2	14001181	00	01	05										
		H3	14001182	00	01	05										
		H4	14001183	00	01	05										
		H5	14001184	00	01	05										
		H6	14001185	00	01	05										
		H7	14001186	00	01	05										
	4.5P	H8	14001187	00	01	05										
		H9	14001188	00	01	05										
		H10	14001189	00	01	05										
		H2	14001190	00	01	05										
		H3	14001191	00	01	05										
		H4	14001192	00	01	05										
		H5	14001193	00	01	05										
		H6	14001194	00	01	05										
10 - 32 UNF	1.5P	H7	14001195	00	01	05							0.1741	0.1776		
		H8	14001196	00	01	05										
		H9	14001197	00	01	05										
		H10	14001198	00	01	05										
	2.5P	H3	14001199	00	01	05										
		H4	14001200	00	01	05										
		H5	14001201	00	01	05										
		H6	14001572	00	01	05										
		H2	14001202	00	01	05										
		H3	14001203	00	01	05										
4.5P	H4	14001204	00	01	05											
	H5	14001205	00	01	05											
	H6	14001206	00	01	05											
	H7	14001207	00	01	05											
5.5P	H8	14001208	00	01	05											
	H9	14001209	00	01	05											

Packed: 1 pc.
EDP's listed above are stocked standard, other coatings available upon request.
Specify treatment at time of order.

continued on next page

Work Material																		
List No.	P					M			K	N		S	H					
	Carbon Steels			Alloy Steels	Die Steels	Stainless Steels			Cast Iron	Aluminum		Nickel Alloy	Titanium	Hardened Steels				
	Low	Med.	High			300	400	17-4 PH		6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC
14001	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
SFM	35-100	20-50	15-25	15-25	15-20	15-40	15-40	10-25		50-90	45-100			10-15				

good best






HY-PRO® NRT

Premium Design for a Wide Range of Materials

List 14001 (Continued)



NRT, Plug (4P-4.5P), Bottom (2P-2.5P), Short Bottom (1P-1.5P)



Units: Inch

Tap Size	Lead	Thread Limit	EDP Number	Coating Suffix			Overall Length L	Thread Length Lc	Neck Length Ln	Shank Dia. d	Square Width k	Square Length lk	Tap Drill Size		Class of Fit	
				Bright	S/O	TiN							Min	Max	2B	3B
10 - 32 UNF	2.5P	H10	14001210	00	01	05	2.375	0.492	0.866	0.194	0.152	0.250	0.1741	0.1776	H6	H4
		H11	14001587	00	-	-										
		H12	14001588	00	-	-										
		H14	14001601	00	-	-										
	4.5P	H2	14001211	00	01	05										
		H3	14001212	00	01	05										
		H4	14001213	00	01	05										
		H5	14001214	00	01	05										
		H6	14001215	00	01	05										
		H7	14001216	00	01	05										
		H8	14001217	00	01	05										
12 - 24 UNC	2.5P	H9	14001218	00	01	05	2.375	0.496	0.933	0.220	0.165	0.281	0.1948	0.1990	H7	H5
		H10	14001219	00	01	05										
		H2	14001220	00	01	05										
		H3	14001221	00	01	05										
		H4	14001222	00	01	05										
		H5	14001223	00	01	05										
		H6	14001224	00	01	05										
		H7	14001225	00	01	05										
		H8	14001226	00	01	05										
		H9	14001227	00	01	05										
	4.5P	H2	14001228	00	01	05										
		H3	14001229	00	01	05										
		H4	14001230	00	01	05										
		H5	14001231	00	01	05										
		H6	14001232	00	01	05										
		H7	14001233	00	01	05										
		H8	14001234	00	01	05										
		H9	14001235	00	01	05										
		H10	14001236	00	01	05										
12 - 28 UNF	2.5P	H10	14001237	00	01	05	2.500	0.594	0.996	0.255	0.191	0.313	0.1978	0.2014	H6	H4
		H2	14001238	00	01	05										
		H3	14001239	00	01	05										
		H4	14001240	00	01	05										
		H5	14001241	00	01	05										
		H6	14001242	00	01	05										
		H7	14001243	00	01	05										
		H8	14001244	00	01	05										
		H9	14001245	00	01	05										
		4.5P	H10	14001246	00	01							05			
	H2		14001247	00	01	05										
	H3		14001248	00	01	05										
	H4		14001249	00	01	05										
	H5		14001250	00	01	05										
	H6		14001251	00	01	05										
	H7		14001252	00	01	05										
	H8		14001253	00	01	05										
	H9		14001254	00	01	05										
	1/4 - 20 UNC	1.5P	H5	14001255	00	01							05	2.500		

Packed: 1 pc.
EDP's listed above are stocked standard, other coatings available upon request.
Specify treatment at time of order.





List 14001 (Continued)



HSS-Co	TiN	S/O	BR
--------	-----	-----	----

NRT, Plug (4P-4.5P), Bottom (2P-2.5P), Short Bottom (1P-1.5P)

Units: Inch

Tap Size	Lead	Thread Limit	EDP Number	Coating Suffix			Overall Length L	Thread Length Lc	Neck Length Ln	Shank Dia. d	Square Width k	Square Length lk	Tap Drill Size		Class of Fit	
				Bright	S/O	TiN							Min	Max	2B	3B
1/4 - 20 UNC	1.5P	H6	14001257	00	01	05	2.375	0.496	0.933	0.255	0.191	0.281	0.2245	0.2296	H6	H4
		H7	14001258	00	01	05										
		H8	14001259	00	01	05										
	2.5P	H2	14001260	00	01	05										
		H3	14001261	00	01	05										
		H4	14001262	00	01	05										
		H5	14001263	00	01	05										
		H6	14001264	00	01	05										
		H7	14001265	00	01	05										
		H8	14001266	00	01	05										
		H9	14001267	00	01	05										
		H10	14001268	00	01	05										
		H11	14001589	00	-	-										
	4.5P	H12	14001590	00	-	-										
		H13	14001591	00	-	-										
		H2	14001269	00	01	05										
		H3	14001270	00	01	05										
		H4	14001271	00	01	05										
		H5	14001272	00	01	05										
		H6	14001273	00	01	05										
1/4 - 28 UNF	1.5P	H7	14001274	00	01	05										
		H8	14001275	00	01	05										
		H9	14001276	00	01	05										
		H10	14001277	00	01	05										
	2.5P	H4	14001278	00	01	05										
		H5	14001279	00	01	05										
		H6	14001280	00	01	05										
		H7	14001281	00	01	05										
		H2	14001282	00	01	05										
		H3	14001283	00	01	05										
		H4	14001284	00	01	05										
		H5	14001285	00	01	05										
		H6	14001286	00	01	05										
		H7	14001287	00	01	05										
	4.5P	H8	14001288	00	01	05										
		H9	14001289	00	01	05										
		H10	14001290	00	01	05										
		H11	14001592	00	-	-										
		H2	14001291	00	01	05										
		H3	14001292	00	01	05										
4.5P	H4	14001293	00	01	05											
	H5	14001294	00	01	05											
	H6	14001295	00	01	05											
	H7	14001296	00	01	05											
	H8	14001297	00	01	05											

Packed: 1 pc.
EDP's listed above are stocked standard, other coatings available upon request.
Specify treatment at time of order.

continued on next page

Work Material																	
List No.	P					M			K	N		S	H				
	Carbon Steels			Alloy Steels	Die Steels	Stainless Steels			Cast Iron	Aluminum		Nickel Alloy	Titanium	Hardened Steels			
	Low	Med.	High			300	400	17-4 PH		6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
14001	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			
SFM	35-100	20-50	15-25	15-25	15-20	15-40	15-40	10-25		50-90	45-100			10-15			

good best






HY-PRO[®] NRT

Premium Design for a Wide Range of Materials

List 14001 (Continued)



NRT, Plug (4P-4.5P), Bottom (2P-2.5P), Short Bottom (1P-1.5P)



Units: Inch

Tap Size	Lead	Thread Limit	EDP Number	Coating Suffix			Overall Length L	Thread Length Lc	Neck Length Ln	Shank Dia. d	Square Width k	Square Length lk	Tap Drill Size		Class of Fit	
				Bright	S/O	TiN							Min	Max	2B	3B
1/4 - 28 UNF	4.5P	H9	14001298	00	01	05	2.375	0.496	0.933	0.255	0.191	0.281	0.2318	0.2354	H6	H4
		H10	14001299	00	01	05										
5/16 - 18 UNC	1.5P	H6	14001300	00	01	05	2.719	0.665	1.126	0.318	0.238	0.375	0.2842	0.2898	H7	H5
		H7	14001301	00	01	05										
		H8	14001302	00	01	05										
		H9	14001303	00	01	05										
		H2	14001304	00	01	05										
	2.5P	H3	14001305	00	01	05										
		H4	14001306	00	01	05										
		H5	14001307	00	01	05										
		H6	14001308	00	01	05										
		H7	14001309	00	01	05										
	4.5P	H8	14001310	00	01	05										
		H9	14001311	00	01	05										
		H10	14001312	00	01	05										
		H11	14001593	00	-	-										
		H2	14001313	00	01	05										
		H3	14001314	00	01	05										
		H4	14001315	00	01	05										
		H5	14001316	00	01	05										
		H6	14001317	00	01	05										
		H7	14001318	00	01	05										
5/16 - 24 UNF	1.5P	H8	14001319	00	01	05	2.719	0.665	1.126	0.318	0.238	0.375	0.2913	0.2955	H7	H5
		H9	14001320	00	01	05										
		H10	14001321	00	01	05										
		H4	14001322	00	01	05										
	2.5P	H5	14001323	00	01	05										
		H6	14001324	00	01	05										
		H7	14001325	00	01	05										
		H8	14001326	00	01	05										
		H2	14001327	00	01	05										
		H3	14001328	00	01	05										
	4.5P	H4	14001329	00	01	05										
		H5	14001330	00	01	05										
H6		14001331	00	01	05											
H7		14001332	00	01	05											
H8		14001333	00	01	05											
H9		14001334	00	01	05											
H10		14001335	00	01	05											
H12		14001594	00	-	-											

Packed: 1 pc.
EDP's listed above are stocked standard, other coatings available upon request.
Specify treatment at time of order.

