

QUICK SLIDE 32

Way and Slide Lubricant

Performance Benefits

- Formulated from high purity hydrocracked base oils
- Low frictional characteristics helps eliminate chatter and stick-slip of slides
- Additive packages designed to meet machine tool requirements for this grade of slideway lubricant
- Excellent water and aqueous separation extends lubricant life and performance of water-based coolants
- Good adhesion prevents removal of lubricant from critical surfaces
- Good rust and corrosion protection helps reduce the deterioration of sliding services and associated maintenance
- Multi-metal compatibility provides protection for ferrous and non-ferrous materials

QUICK SLIDE 32 is a light viscosity premium-quality slide way lubricant specifically designed for machine tools fitted with combined hydraulic and slideway lubrication systems. It is formulated with high-quality base stocks and a highly engineered additive package designed to reduce stick-slip and chatter under thin film, boundary lubrication conditions allowing smooth uniform motion at travel speeds of today's advanced machinery.

QUICK SLIDE 32 ensures protection of slides and ways while still providing good filterability thereby minimizing reduced flow or plugged applicator filters.

Applications

QUICK SLIDE 32 is recommended for machine tools which require an ISO VG 32 Slideway Lubricant

Typical Characteristics

Appearance.....	Clear, light amber viscous liquid
Kinematic Viscosity.....	32cSt @ 40°C
ISO grade.....	32
Copper Strip (ASTM D 130).....	1B
Flash, PMCC	>200°C

Recommended Dilutions

QUICK SLIDE 32 is designed to be applied neat.

Packaging

QUICK SLIDE 32 is packaged 5-gallon pails and 55-gallon non-returnable steel drums. Bulk and 310-gallon bins are also available.