

QUICK SLIDE 68

Way and Slide Lubricant

Performance Benefits

- Formulated from high purity hydrocracked base oils
- Low frictional characteristics helps eliminate chatter and stick-slip of slides
- Additive packages designed to meet machine tool requirements for this grade of slideway lubricant
- Good adhesion prevents removal of lubricant from critical surfaces
- Good rust and corrosion protection helps reduce the deterioration of sliding services and associated maintenance
- Multi-metal compatibility provides protection for ferrous and non-ferrous materials
- Good water and aqueous separation extends lubricant life and performance of water-based coolants

QUICK SLIDE 68 is a premium-quality slideway lubricant specifically designed to meet the strict requirements for accuracy and part finish of today's high production machine tools. It is formulated with high-quality base stocks and a highly engineered additive package designed to reduce stick-slip and chatter under thin film, boundary lubrication conditions allowing smooth uniform motion at travel speeds of today's advanced machinery.

QUICK SLIDE 68 ensures protection of slides and ways while still providing good filterability thereby minimizing reduced flow or plugged applicator filters.

QUICK SLIDE 68 is approved under Cincinnati Machine P-47 specification.

Applications

QUICK SLIDE 68 is recommended for machine tools which require an ISO VG 68 Slideway Lubricant.

Typical Characteristics

Appearance.....	Clear, light yellow liquid
Viscosity.....	315 SUS @40°C
ISO grade.....	68
Copper Strip (ASTM D 130).....	1B
Flash Pt. (COC).....	>450°F (232°C)

Recommended Dilutions

QUICK SLIDE 68 is designed to be applied neat

Packaging

QUICK SLIDE 68 is packaged 5-gallon pails and 55-gallon non-returnable steel drums. Bulk and 310-gallon bins are also available.