

XTREME GRIND 311C

Premium Blanchard Grinding Synthetic

Performance Benefits

- Improved dimensional accuracy, fine finishes, and reduced rework rates resulting from state-of-the-art technology
- Low foaming in both soft and hard water
- Excellent corrosion control
- Wheels kept clean and free cutting
- Quick chip settling to reduce wheel loading
- Complete rejection of tramp oil
- Long system/sump life due to good bacterial and fungal protection
- Formaldehyde free to comply with health and safety regulations

XTREME GRIND 311C is an oil rejecting synthetic fluid designed for Blanchard grinding. The low foaming properties also make this product an excellent choice for a wide variety of grinding applications such as double disk and surface grinding.

XTREME GRIND 311C is also suitable for use as a rust preventative for pressure testing tanks.

Typical Characteristics

Appearance of concentrate.....Clear, colorless liquid
 Density.....8.76 lbs./gal
 Specific gravity.....1.05
 pH of 5% solution.....9.1-9.5

XTREME GRIND 311C does not contain as an ingredient: Chlorine, Nitrite, Phenols, or Silicones.

Recommended Dilutions

XTREME GRIND 311C is to be mixed with water for use (add concentrate to water).
 Grinding: 3-7%

Concentration Control

The chart below was prepared using an Atago Master M refractometer and dilutions of **XTREME GRIND 311C** in distilled water. Refractometer readings can vary with the type of water and refractometer used. Atago Master M refractometers are available from QualiChem, Inc.

CONCENTRATION %:	3	4	5	6
REFRACTOMETER READING:	0.8	1.1	1.4	1.7

Packaging

XTREME GRIND 311C is packaged in 310-gallon, one-way tote tanks and 55-gallon, non-returnable steel drums. Bulk and 5-gallon pails are also available.

QUALICHEM
 Metalworking Fluids

AN ISO 9001:2008 COMPANY
 2003 Salem Industrial Drive | Salem, VA 24153
 540.375.6700
www.qualichem.com/metalworking