



## Safety Data Sheet

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	10-3199-6	<b>Version Number:</b>	30.00
<b>Issue Date:</b>	11/25/14	<b>Supersedes Date:</b>	10/05/12

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Weatherban™ Butyl Sealant Tape 5354

#### Product Identification Numbers

62-5354-0101-2, 62-5354-1041-9, 62-5354-1042-7, 62-5354-1270-4, 62-5354-1271-2, 62-5354-1275-3, 62-5354-1350-4

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Solid sealer on roll, Industrial use

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Industrial Adhesives and Tapes Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### 2.2. Label elements

##### Signal word

Not applicable.

##### Symbols

Not applicable.

##### Pictograms

Not applicable.

#### 2.3. Hazards not otherwise classified

None.

### SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Polybutylene	9003-29-6	20 - 35 Trade Secret *
Kaolin	1332-58-7	20 - 35 Trade Secret *
Carbon Black	1333-86-4	15 - 30 Trade Secret *
Isobutylene-Isoprene Polymer	9010-85-9	1 - 15 Trade Secret *
Glycerol Ester of Hydrogenated Rosin	65997-13-9	1 - 5 Trade Secret *
Talc	14807-96-6	1 - 5 Trade Secret *
Solvent-Refined Heavy Paraffinic Petroleum Distillates	64741-88-4	< 4 Trade Secret *
Titanium Dioxide	13463-67-7	< 2 Trade Secret *
Quartz silica	14808-60-7	< 1 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

**Inhalation:**

No need for first aid is anticipated.

**Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

Non-combustible. Use a fire fighting agent suitable for surrounding fire.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### Hazardous Decomposition or By-Products

**Substance**

Carbon monoxide

Carbon dioxide

**Condition**

During Combustion

During Combustion

#### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Observe precautions from other sections.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid eye contact. For industrial or professional use only. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Kaolin	1332-58-7	ACGIH	TWA(respirable fraction):2 mg/m <sup>3</sup>	A4: Not class. as human carcin
KAOLIN, TOTAL DUST	1332-58-7	OSHA	TWA(as total dust):15 mg/m <sup>3</sup> ;TWA(respirable fraction):5 mg/m <sup>3</sup>	
Carbon Black	1333-86-4	CMRG	TWA:0.5 mg/m <sup>3</sup>	
Carbon Black	1333-86-4	OSHA	TWA:3.5 mg/m <sup>3</sup>	
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m <sup>3</sup>	A3: Confirmed animal carcin.
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m <sup>3</sup>	
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m <sup>3</sup>	A4: Not class. as human carcin
Titanium Dioxide	13463-67-7	CMRG	TWA(as respirable dust):5 mg/m <sup>3</sup>	
Talc	14807-96-6	OSHA	TWA concentration(as total dust):0.3 mg/m <sup>3</sup> ;TWA concentration(respirable):0.1 mg/m <sup>3</sup> (2.4 millions of particles/cu. ft.);TWA:20 millions of particles/cu. ft.	
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m <sup>3</sup>	A4: Not class. as human carcin
Talc	14807-96-6	CMRG	TWA(as respirable dust):0.5	

			mg/m3	
Quartz silica	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.
Quartz silica	14808-60-7	OSHA	TWA concentration(as total dust):0.3 mg/m3;TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.)	
Paraffin oil	64741-88-4	OSHA	TWA(as mist):5 mg/m3	
Mineral oils (untreated and mildly treated)	64741-88-4	ACGIH	Limit value not established:	Cntrl all exposr-low as possib, A2: Suspected human carcin.
MINERAL OILS, HIGHLY-REFINED OILS	64741-88-4	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
PETROLEUM DISTILLATES	64741-88-4	OSHA	TWA:2000 mg/m3(500 ppm)	
Solvent-Refined Heavy Paraffinic Petroleum Distillates	64741-88-4	CMRG	TWA:5 mg/m3	
Rosin	65997-13-9	ACGIH	Limit value not established:	Cntrl all exposr-low as possib, Dermal/Respiratory Sensitizer

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

None required.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

#### Respiratory protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

General Physical Form: Solid

<b>Specific Physical Form:</b>	Extruded bead on roll
<b>Odor, Color, Grade:</b>	Black
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>No Data Available</i>
<b>Boiling Point</b>	<i>Not Applicable</i>
<b>Evaporation rate</b>	<i>Not Applicable</i>
<b>Flammability (solid, gas)</b>	Not Classified
<b>Flammable Limits(LEL)</b>	<i>Not Applicable</i>
<b>Flammable Limits(UEL)</b>	<i>Not Applicable</i>
<b>Vapor Pressure</b>	<i>Not Applicable</i>
<b>Vapor Density</b>	<i>Not Applicable</i>
<b>Density</b>	1.41 g/ml
<b>Specific Gravity</b>	1.410 [ <i>Ref Std: WATER=1</i> ]
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Hazardous Air Pollutants</b>	0 % weight [ <i>Test Method: Calculated</i> ]
<b>Volatile Organic Compounds</b>	0 g/l [ <i>Details: EU VOC content</i> ]
<b>Percent volatile</b>	0.0 % weight
<b>VOC Less H2O &amp; Exempt Solvents</b>	0 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

#### Substance

None known.

#### Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

## 11.1. Information on Toxicological effects

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

No health effects are expected.

#### Skin Contact:

Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

#### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYSTAL AIRRESP	14808-60-7	Known human carcinogen	National Toxicology Program Carcinogens
Carbon Black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Quartz silica	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
Polybutylene	Dermal	Rat	LD50 > 10,250 mg/kg
Polybutylene	Ingestion	Rat	LD50 > 34,600 mg/kg
Kaolin	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolin	Ingestion	Human	LD50 > 15,000 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg
Isobutylene-Isoprene Polymer	Ingestion		LD50 estimated to be > 5,000 mg/kg
Talc	Dermal		LD50 Not available
Talc	Ingestion		LD50 Not available
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Dermal	Rabbit	LD50 > 2,000 mg/kg
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Ingestion	Rat	LD50 > 5,000
Glycerol Ester of Hydrogenated Rosin	Dermal	Rat	LD50 > 2,000 mg/kg
Glycerol Ester of Hydrogenated Rosin	Ingestion	Rat	LD50 > 2,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Quartz silica	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz silica	Ingestion		LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Polybutylene	Rabbit	Minimal irritation
Kaolin		No significant irritation

Carbon Black	Rabbit	No significant irritation
Isobutylene-Isoprene Polymer	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Rabbit	Minimal irritation
Glycerol Ester of Hydrogenated Rosin	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation
Quartz silica		No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Polybutylene	Rabbit	Mild irritant
Kaolin		No significant irritation
Carbon Black	Rabbit	No significant irritation
Isobutylene-Isoprene Polymer		No significant irritation
Talc	Rabbit	No significant irritation
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Rabbit	Mild irritant
Glycerol Ester of Hydrogenated Rosin	Rabbit	Mild irritant
Titanium Dioxide	Rabbit	No significant irritation

**Skin Sensitization**

Name	Species	Value
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Guinea pig	Not sensitizing
Glycerol Ester of Hydrogenated Rosin	Human and animal	Not sensitizing
Titanium Dioxide	Human and animal	Not sensitizing

**Respiratory Sensitization**

Name	Species	Value
Talc	Human	Not sensitizing

**Germ Cell Mutagenicity**

Name	Route	Value
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Solvent-Refined Heavy Paraffinic Petroleum Distillates	In Vitro	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
Quartz silica	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz silica	In vivo	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Kaolin	Inhalation	Multiple animal species	Not carcinogenic
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic

Titanium Dioxide	Inhalation	Rat	Carcinogenic
Quartz silica	Inhalation	Human and animal	Carcinogenic

## Reproductive Toxicity

### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Talc	Ingestion	Not toxic to development	Rat	NOAEL 1,600 mg/kg	during organogenesis

## Target Organ(s)

### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Polybutylene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.07 mg/l	2 weeks
Polybutylene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.7 mg/l	2 weeks
Kaolin	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Kaolin	Inhalation	pulmonary fibrosis	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	
Carbon Black	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis   respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 18 mg/m <sup>3</sup>	113 weeks
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.21 mg/l	28 days
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.010 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	All data are negative	Human	NOAEL Not available	occupational exposure
Quartz silica	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure

## Aspiration Hazard

Name	Value
Solvent-Refined Heavy Paraffinic Petroleum Distillates	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information



on this material and/or its components.

## SECTION 12: Ecological information

### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** Not regulated

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No    Pressure Hazard - No    Reactivity Hazard - No    Immediate Hazard - Yes    Delayed Hazard - No

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

Health: 1 Flammability: 0 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	10-3199-6	<b>Version Number:</b>	30.00
<b>Issue Date:</b>	11/25/14	<b>Supersedes Date:</b>	10/05/12

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at [www.3M.com](http://www.3M.com)