

June, 2015

3M™ Textile Flatback Tape 2526

Product Description

3M™ Textile Flatback Tape 2526 is used in the textile industry where high adhesion strength and high holding are required.

Product Features

- Has excellent adhesion and backing strength levels and is resistant to moist conditions.
- Can withstand a bake cycle up to 300°F (149°C) for 30 minutes. The actual time and temperature performance may be higher or lower for a given application.
- Not recommended for outdoor applications or prolonged periods of sunlight exposure as tape may become very difficult to remove.
- This tape exhibits excellent holding power of textile fibers. Clean removal can vary dependent on surface type, processing conditions, heat cycles and temperature of the surface at removal. We recommend testing the product under your conditions to determine if it meets your needs.



3M™ Textile Flatback Tape 2526

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Method
Color	White		
Total Tape Thickness	0.242 mm	9.8 mil	ASTM D3652
Backing	Flat stock paper		
Adhesive	Natural Rubber		

Typical Performance Characteristics

Property	Values		Method	Substrate
Peel Adhesion	7.5 N/cm	69 oz/in	ASTM D3330	Stainless Steel
Tensile Strength	85.8 N/cm	50 lb/in	ASTM D3759	
Elongation at Break	4 %		ASTM D3759	
Temperature Use Range	Up to 149 °C	Up to 300 °F		

Available Sizes

Property	Values		Notes
Standard Roll Length	55 m	60 yd	Available in metric widths (eg, 24 mm corresponds to 1 inch).

3M™ Textile Flatback Tape 2526

Handling/Application Information

Application Ideas

Can be used in many holding, tabbing, and leasing of natural and synthetic fiber applications where a performance flatback tape is desired. It can also be used for various types of edging, splicing and holding applications.

Storage and Shelf Life

Store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.
To obtain best performance, use this product within 18 months from date of manufacture.

Trademarks

3M is a trademark of 3M Company.

References

Safety Data Sheet (SDS)

https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=2526

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.

Technical Information

The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

3M™ Textile Flatback Tape 2526

Product Selection and Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer

Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



Industrial Adhesives and Tapes
Division
3M Center
St. Paul, MN 55144-1000
800-362-3550
www.3M.com

Please recycle.
© 3M 2019. All Rights
Reserved.

The brands listed above are trademarks of
3M