uminum Repair Procedures

Sealing and Coating Coating Anti **Pre-Cleaning** Prewash/clean vehicle prior to disassembly (power wash undercarriage area at repair). Removal of Heavy Surface Contaminates Clean to remove heavy contaminants from repair area. **OEM Coating Removal** Remove OEM coating as needed using Clean N Strip disc. Featheredge using grade 80 abrasive on DA sander. Blow off surface with clean, dry air. Clean surface with all purpose cleaner and degreaser. Filling/Leveling Surface Use polyester glaze to fill the repair area, bringing it the same level as the surrounding coating.

Sanding and Primer

Sand glaze using P150 on a hand block. Final featheredge area using P320 abrasive on a DA sander. Blow off with clean, dry air. Final clean with VOC compliant wax and grease remover. Apply primer following paint company recommendations.

Sanding Primer

Apply 3M guide coat to primed surface. Sand primer using P320 on a DA sander with an interface pad. Blow off with clean, dry air. Final clean with VOC compliant wax and grease remover.

Masking

Apply soft edge foam masking tape following existing coating edge. Final mask the area using tape and paper to protect from

Coating Test Panel

Apply the coating to a test panel. Always apply a light coat first, allow it to flash, and adjust the spray equipment to deliver the texture required to match the OEM appearance.

Apply Coating

Apply anti chip coating to the repair area using settings from test panel, blending the material into surrounding area as needed.

Blend Sanding

Use P1000 3M™ Trizact™ Disc on a DA sander to smooth the blend edges. This operation produces a smooth transition without removing chip coating profile.

Visit www.3MCollision.com for more SOPs and videos

Product List

3M™ Car Wash Soap Concentrate, 1 gallon, PN 38377

3M™ All Purpose Cleaner and Degreaser Concentrate, 1 gallon, PN 38350





3M™ General Purpose Adhesive Cleaner, aerosol, PN 08987: Adhesive Remover, PN 38983



Scotch-Brite™ Roloc™+ Clean N Strip XT Disc, PN 07470; TR Disc, PN 07466



3M™ Cubitron™ II Clean Sanding Hookit™ Abrasive Disc, 6 in., 80+ grade, PN 31371



3M™ Platinum™ Plus Finishing Glaze, 30 oz., PN 31180; Glaze for DMS, PN 05862





3M™ Hookit™ Purple Clean Sanding Sheet Roll, 150 grade, 70mm x 12m, PN 30710; Disc 334U, 6 in., P320 grit, PN 01812



3M™ Hookit™ Sanding Block Dust Free 70mm x 127mm, PN 05207





3M™ Hookit™ Soft Interface Pad. 6 in. x 1/2 in. x 3/4 in., PN 05777



3M™ Soft Edge Foam Masking Tape PLUS, 21mm (.8 in.), PN 06293



3M™ Smooth Transition Tape, 1/4 in. (6.4mm), PN 06800



3M™ Scotchblok™ Masking Paper, 18 in. x 180 ft., PN 06738



Scotch® Performance Green Masking Tape 233+,



12mm width (.47 in.), PN 26332



3M™ Rocker Protector Pouch, 3 fl. oz. (US), PN 08733; 5.5 fl. oz. (US), PN 08734



3M™ Paintable Undercoating. Waterbased — Pouch. 5.5 fl. oz. (US), PN 08744



3M™ Trizact™ Hookit™ Blending Disc, 6 in., P1000 grit, PN 02090



Think About Your Health

3M[™] E-A-R[™] Skull Screws[™] Ear Plug, PN P1300



3M™ Respirator Assembly/Organic Vapor N95 Dual Cartridge. PN 07192



3M™ Lexa™ Protective Eyewear, PN 15200

