



Document Library
Technical Data Sheet 06706; 06712;
06718; 06736; 06732; 06738

Public

Rev:1

Effective: 10/04/2007

Status: Active

3M™ Scotchblok™ Masking Paper

Data Sheet

3M Part No.(s)	3M Part Descriptor(s)
06706	6" x 750 ft - 6 rolls/case
06712	12" x 750 ft - 3 rolls/case
06718	18" x 750 ft - 2 rolls/case
06736	36" x 750 ft - 1 roll/case
06732	12" x 180 ft - 12 rolls/case
06738	18" x 180 ft - 12 rolls/case

3M Fax on Demand Identification Number :

Description

3M™ Scotchblok Masking Paper is tightly bonded, specially coated and manufactured specifically for automotive aftermarket applications. It is designed to be used with 3M masking tapes and 3M masking equipment.

Features, Advantages, Benefits

Features	<ol style="list-style-type: none"> 1. Special poly coating 2. Thin paper 3. Easy tear
Advantages	<ol style="list-style-type: none"> 1. No solvent penetration 2. More conformable 3. Excellent performance on apron tapers and maskers
Benefits	<ol style="list-style-type: none"> 1. Eliminates rework caused by bleed-through 2. Easy to handle to help increase productivity 3. Reduces paper waste

Typical Physical Properties

Basis Weight	21 lbs/3000 square ft	ASTM D-3759
Machine Direction Tensile	15 lbs/inch width	ASTM D-3759
Mullen Burst Strength	17 lbs/square inch	ASTM D-3759
Caliper	2 mil (0.051mm)	ASTM D-3652

Product Uses

Designed for use with 3M Masking Tapes and 3M Masking Equipment. Gross masking products intended to protect surfaces from paint overspray and solvent bleed-through.

Performance Properties

- Ultimate penetration resistance from all solvents used in automotive aftermarket repairs and refinishing.
- Protects against dust contamination from paper fibers
- Provides excellent conformability
- Holds up well under wet sanding conditions
- Withstands bake cycles up to 225 degrees F (107 degrees C) for up to 30 minutes
- Distinctive gold color for easy identification

Handling and Application Information

Directions for Use

Applications

Storage and Handling

For best performance, product should be used within one year of the date of manufacture. Product should be stored in the original carton under normal conditions of 70 degrees F (21 degrees C) and 50% RH (relative humidity).

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for Health and Safety Information before using this product

Country

US

This document is public. It may be distributed.

Warranty and Limited Remedy

This product will be free from defects in material and workmanship at the time of shipment. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If this product is defective, your exclusive remedy and 3M's and seller's sole obligation shall be, at 3M's option, to replace the product or refund the purchase price.

LIMITATION OF LIABILITY: 3M and seller will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

For Additional Health and Safety Information

3M Automotive Aftermarket Division

3M Center, Building 223-6N-01

Saint Paul, MN 55144-1000

1-877-666-2277 (1-877-MMM-CARS)

Material Safety Data Sheets and Technical Data Sheets are also available by calling Fax on Demand 1-800-305-0419.

Help Line 1-800-621-5455 (US) 1-650-596-4407 (International).

3M Fax on Demand/MSDS Identification Number

Author: Sandy J. Libby/US-Corporate/3M/US

Modifiers: Sandy J. Libby/US-Corporate/3M/US

This is the last page