



Document Library
TS Data Sheet 08506;
08509

Public

Rev:1

Effective: 06/27/99

Status: Active

Automotive Bedding and Glazing Compound

Data Sheet

3M Part No.(s) **3M Part Descriptor(s)**

08506;
08509

3M Fax on Demand Identification Number:

Description

A non-hardening, pliable, water resistant sealer for sealing between windshield rubber and car body.

This product remains permanently soft.

The product has a non-sag consistency for vertical and overhead applications.

Features, Advantages, Benefits

Features

Advantages

Benefits

Typical Physical Properties

Container	1/10 Gallon Cartridge	
Base	Synthetic Rubber	
Color	Neutral (08506)	Black (08509)
Flash Point - °F	Greater than 100°F	
Solids Content (Appx.)	90%	
Solvent	Petroleum Distillates	

Product Uses

Performance Properties

Handling and Application Information

Directions for Use

- Remove all dirt, grease and old sealant.
- Clean with 3M General Purpose Adhesive Cleaner P.N. 08984 if dirty.
- Cut tip at least 1/2" from end and puncture seal in spout.
- Apply sealer between car body and rubber windshield gasket.
- Clean excess sealer with dry rag.

Applications

Storage and Handling

Store at room temperature. Rotate stock on a "first-in-first-out" basis. When stored at the recommended conditions in original, unopened containers, this product has a shelf life of 12 months.

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for Health and Safety Information before using this product.

Country

US

This document is public. It may be distributed.

Important Notice to Purchaser

The statements and technical information contained in this technical data sheet are based on tests and data which 3M believes to be reliable, but the accuracy or completeness of such statements and technical information is not guaranteed. **3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of application.

* If 'Directions for Use' reference P.N.'s 8984, 8986, or 8987, please read below.

Federal and local air quality regulations may regulate or prohibit the use of surface preparation and cleanup solvents based on VOC content. Consult your local and Federal air quality regulations for information. When using solvents, use in a well ventilated area. Extinguish all sources of ignition in the work area and observe precautionary measures for handling these materials. Refer to product label and MSDS for P.N. 8984, 8986, or 8987 for detailed precautionary information.

LIMITATION OF REMEDIES AND LIABILITY: If the 3M product is proved to be defective, **THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT.**

3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

For Additional Health and Safety Information

See Material Safety Data Sheet (Fax on Demand 1-800-305-0419), or call: **3M Automotive Aftermarket Division** 3M Center, Building 223-6N-01
Phone: 877-MMM-CARS (877-666-2277)

3M Fax on Demand Identification Number

Reference: Goto Ref

Author:

Karen A. Licht/US-Corporate/3M/US
Tonya L. Frisle/IM-IndMktsGp/3M/US

This is the last page