

"All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. The results reported herein are based solely on the limited sample provided to us for testing under laboratory conditions and are NOT intended to be representative of typical product performances.

3M shall not be liable in tort or in contract for any injury, loss or damage, direct, indirect, special or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for user's intended use, and user assumes all risks and liability whatsoever in connection therewith."

### **3M 336I Production™ Paper**

Product	336I
Construction	Aluminum Oxide is coated on to a C weight backing. The available grade range is 100, 120 and 150. Construction is open coat.
Application Areas	Used primarily for wood sanding in sheet and disc form. Dry use only.
Features	C weight provides extra strength and stiffness compared to A weight products. This is an Express Plus Catalog item.
Max. Available Width	9 in (228.6 mm)

### **Available Converted Forms (\*)**

#### **Belts**

Regular  
Segment  
Clipped

#### **Discs**

\* Regular  
Roloc™  
\* Delappe  
Overlap slotted

#### **Evenrun**

\* Bands  
\* Belts

#### **Rolls**

\* Regular  
Scored  
\* Serrated  
Slit down  
Cartridge

#### **Stikit™**

Disc/roll  
Sheet/roll  
Refill rolls  
Individual discs  
Individual sheets

#### **Other**

PG wheels  
RX segments  
Slashed assemblies  
\* Sheets  
Cones