

# Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 25-1257-2
 Version Number:
 5.00

 Issue Date:
 05/19/21
 Supercedes Date:
 06/28/19

# **SECTION 1: Identification**

#### 1.1. Product identifier

3M(TM) Screen Printing Ink 1903 White

# **Product Identification Numbers**

75-3469-4417-8 7000005188

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Ink

1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** Commercial Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

**Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

# 2.1. Hazard classification

Flammable Liquid: Category 3.

Serious Eye Damage/Irritation: Category 1. Skin Corrosion/Irritation: Category 2. Skin Sensitizer: Category 1A.

Reproductive Toxicity: Category 2. Carcinogenicity: Category 2.

Specific Target Organ Toxicity (single exposure): Category 3.

# 2.2. Label elements

# Signal word

Danger

#### **Symbols**

Flame | Corrosion | Exclamation mark | Health Hazard |

# **Pictograms**



#### **Hazard Statements**

Flammable liquid and vapor.

Causes serious eye damage.

Causes skin irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

Suspected of damaging fertility or the unborn child.

Suspected of causing cancer.

### **Precautionary Statements**

#### **Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

# **Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### Storage:

Keep container tightly closed.

Keep cool.

Store locked up in a well-ventilated place.

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

14% of the mixture consists of ingredients of unknown acute oral toxicity.

16

14% of the mixture consists of ingredients of unknown acute dermal toxicity. 14% of the mixture consists of ingredients of unknown acute inhalation toxicity.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Titanium Dioxide	13463-67-7	20 - 65 Trade Secret *
CYCLOHEXANONE	108-94-1	20 - 30 Trade Secret *
ETHYL 3-ETHOXYPROPIONATE	763-69-9	10 - 20 Trade Secret *
VINYL ACETATE-VINYL ALCOHOL-VINYL	25086-48-0	5 - 15 Trade Secret *
CHLORIDE POLYMER		
2-BUTOXYETHYL ACETATE	112-07-2	5 - 10 Trade Secret *
ACRYLIC POLYMER	Trade Secret*	5 - 10 Trade Secret *
POLYMERIC PLASTICIZER	Trade Secret*	3 - 7 Trade Secret *
EPOXIDIZED SOYBEAN OIL	8013-07-8	1 - 5 Trade Secret *
ALUMINUM OXIDE	1344-28-1	< 1.5 Trade Secret *
Silica	7631-86-9	< 1.5 Trade Secret *
ALUMINUM (CALCULATED AS AL2O3)	None	< 1.5 Trade Secret *
AMORPH. SILICA (CALCULATED AS SIO2)	None	< 1.5 Trade Secret *
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	41556-26-7	< 1 Trade Secret *
HEAVY AROMATIC SOLVENT NAPHTHA	64742-94-5	< 1 Trade Secret *
(PETROLEUM)		
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-	104810-48-2	< 1 Trade Secret *
2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-		
oxopropyl]omegahydroxy-		
Polymeric Benzotriazole	104810-47-1	< 1 Trade Secret *
ZINC 2-ETHYLHEXANOATE	136-53-8	< 1 Trade Secret *
Naphthalene	91-20-3	< 0.1 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

# 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

# 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### **Hazardous Decomposition or By-Products**

SubstanceConditionCarbon monoxideDuring CombustionCarbon dioxideDuring CombustionHydrogen ChlorideDuring Combustion

# 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing

agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

# 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight. Store away from heat. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

# Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
CYCLOHEXANONE	108-94-1	ACGIH	TWA:20 ppm;STEL:50 ppm	A3: Confirmed animal carcin., Danger of cutaneous absorption
CYCLOHEXANONE	108-94-1	OSHA	TWA:200 mg/m3(50 ppm)	
2-BUTOXYETHYL ACETATE	112-07-2	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin.
ALUMINUM OXIDE	1344-28-1	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m3	A4: Not class. as human carcin
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
SILICA, AMORPHOUS	7631-86-9	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	
Naphthalene	91-20-3	ACGIH	TWA:10 ppm	A3: Confirmed animal carcin., Danger of cutaneous absorption
Naphthalene	91-20-3	OSHA	TWA:50 mg/m3(10 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

# 8.2.2. Personal protective equipment (PPE)

# Eye/face protection

\_\_\_\_

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

# **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid Color White

Specific Physical Form:

Odor

Liquid
Solvent

Odor thresholdNo Data AvailablepHNot ApplicableMelting pointNot ApplicableBoiling Point>=312 °F

Flash Point 120 °F [Test Method: Closed Cup]

Evaporation rate

No Data Available
Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL) .5 %
Flammable Limits(UEL) 8.7 %

 Vapor Pressure
 <=3.4 mmHg [@ 20 °C]</td>

 Vapor Density
 > 1 [Ref Std: AIR=1]

 Possition
 1.48 g/ml

**Density** 1.48 g/ml

Specific Gravity 1.48 [Ref Std:WATER=1]

**Solubility in Water** Moderate

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data Available

**Autoignition temperature** > 640 °F

**Decomposition temperature**No Data Available

Viscosity 5,000 - 7,000 centipoise [Test Method: Tested per ASTM

**Page** 6 **of** 16

protocol]

**Volatile Organic Compounds** 607 g/l [*Details*: As formulated]

**Volatile Organic Compounds** 686 g/l [Details: After manufacturing thinning]

**Percent volatile** 35.0 - 45.0 %

VOC Less H2O & Exempt Solvents 607 g/l [Details: As formulated]

VOC Less H2O & Exempt Solvents 686 g/l [Details: After manufacturing thinning]

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

# 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

Sparks and/or flames

# 10.5. Incompatible materials

Strong oxidizing agents

### 10.6. Hazardous decomposition products

**Substance** Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### **Inhalation:**

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

#### **Skin Contact:**

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

# **Eve Contact:**

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### **Ingestion:**

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

### **Additional Health Effects:**

#### Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

# Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

# Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	CAS No.	Class Description	Regulation
Naphthalene	91-20-3	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Naphthalene	91-20-3	Anticipated human carcinogen	National Toxicology Program Carcinogens
Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

# **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal	Species	No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
CYCLOHEXANONE	Dermal	Rabbit	LD50 >794, <3160 mg/kg
CYCLOHEXANONE	Inhalation- Vapor (4 hours)	Rat	LC50 > 6.2 mg/l
CYCLOHEXANONE	Ingestion	Rat	LD50 1,296 mg/kg
ETHYL 3-ETHOXYPROPIONATE	Dermal	Rabbit	LD50 4,080 mg/kg
ETHYL 3-ETHOXYPROPIONATE	Inhalation- Vapor (4 hours)	Rat	LC50 > 14.4 mg/l
ETHYL 3-ETHOXYPROPIONATE	Ingestion	Rat	LD50 3,200 mg/kg
VINYL ACETATE-VINYL ALCOHOL-VINYL CHLORIDE POLYMER	Dermal	Rabbit	LD50 > 8,000 mg/kg

**Page** 8 **of** 16

VINYL ACETATE-VINYL ALCOHOL-VINYL CHLORIDE	Ingestion	Rat	LD50 > 8,000 mg/kg
POLYMER	ingestion	Kat	LD30 > 0,000 mg/kg
2-BUTOXYETHYL ACETATE	Dermal	Rabbit	LD50 > 4,766 mg/kg
2-BUTOXYETHYL ACETATE	Inhalation- Vapor (4 hours)	Rat	LC50 > 2.66 mg/l
2-BUTOXYETHYL ACETATE	Ingestion	Rat	LD50 1,880 mg/kg
EPOXIDIZED SOYBEAN OIL	Dermal	Rabbit	LD50 > 20,000 mg/kg
EPOXIDIZED SOYBEAN OIL	Ingestion	Rat	LD50 > 5,000 mg/kg
Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
ALUMINUM OXIDE	Dermal		LD50 estimated to be > 5,000 mg/kg
ALUMINUM OXIDE	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
ALUMINUM OXIDE	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	Dermal	Rat	LD50 > 2,000 mg/kg
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.8 mg/l
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	Ingestion	Rat	LD50 > 5,000 mg/kg
Polymeric Benzotriazole	Dermal	Rat	LD50 > 2,000 mg/kg
Polymeric Benzotriazole	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.8 mg/l
Polymeric Benzotriazole	Ingestion	Rat	LD50 > 5,000 mg/kg
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Inhalation- Vapor		LC50 estimated to be 20 - 50 mg/l
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Dermal	Rabbit	LD50 > 2,000 mg/kg
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Ingestion	Rat	LD50 > 5,000 mg/kg
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Ingestion	Rat	LD50 3,125 mg/kg
ZINC 2-ETHYLHEXANOATE	Dermal		LD50 estimated to be > 5,000 mg/kg
ZINC 2-ETHYLHEXANOATE	Ingestion	Rat	LD50 > 5,000 mg/kg
Naphthalene	Dermal	Human	LD50 estimated to be 2,000 - 5,000 mg/kg
Naphthalene	Inhalation- Vapor	Human	LC50 estimated to be 20 - 50 mg/l
Naphthalene	Ingestion	Human	LD50 estimated to be 300 - 2,000 mg/kg

ATE = acute toxicity estimate

# Skin Corrosion/Irritation

Name	Species	Value
Titanium Dioxide	Rabbit	No significant irritation
CYCLOHEXANONE	Rabbit	Irritant
ETHYL 3-ETHOXYPROPIONATE	Rabbit	No significant irritation
VINYL ACETATE-VINYL ALCOHOL-VINYL CHLORIDE POLYMER	Professio	No significant irritation
	nal	
	judgeme	
	nt	
2-BUTOXYETHYL ACETATE	Rabbit	Minimal irritation
EPOXIDIZED SOYBEAN OIL	Rabbit	No significant irritation
Silica	Rabbit	No significant irritation
ALUMINUM OXIDE	Rabbit	No significant irritation
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-	Rabbit	No significant irritation
dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-		
Polymeric Benzotriazole	Rabbit	No significant irritation

**Page** 9 **of** 16

HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Rabbit	Minimal irritation
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Rabbit	No significant irritation
ZINC 2-ETHYLHEXANOATE	Rabbit	Mild irritant
Naphthalene	Rabbit	Minimal irritation

**Serious Eye Damage/Irritation** 

Name	Species	Value
Titanium Dioxide	Rabbit	No significant irritation
CYCLOHEXANONE	In vitro	Corrosive
	data	
ETHYL 3-ETHOXYPROPIONATE	Rabbit	Mild irritant
VINYL ACETATE-VINYL ALCOHOL-VINYL CHLORIDE POLYMER	Professio	No significant irritation
	nal	
	judgeme	
	nt	
2-BUTOXYETHYL ACETATE	Rabbit	Mild irritant
EPOXIDIZED SOYBEAN OIL	Rabbit	No significant irritation
Silica	Rabbit	No significant irritation
ALUMINUM OXIDE	Rabbit	No significant irritation
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-	Rabbit	No significant irritation
dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-		
Polymeric Benzotriazole	Rabbit	No significant irritation
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Rabbit	Mild irritant
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Rabbit	No significant irritation
ZINC 2-ETHYLHEXANOATE	Rabbit	Severe irritant
Naphthalene	Rabbit	No significant irritation

# **Skin Sensitization**

Name	Species	Value
Titanium Dioxide	Human	Not classified
	and	
	animal	
CYCLOHEXANONE	Guinea	Not classified
	pig	
ETHYL 3-ETHOXYPROPIONATE	Guinea	Not classified
	pig	
2-BUTOXYETHYL ACETATE	Guinea	Not classified
	pig	
EPOXIDIZED SOYBEAN OIL	Guinea	Not classified
	pig	
Silica	Human	Not classified
	and	
	animal	
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-	Guinea	Sensitizing
dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	pig	
Polymeric Benzotriazole	Guinea	Sensitizing
	pig	
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Guinea	Not classified
	pig	
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Guinea	Sensitizing
	pig	

# **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
CYCLOHEXANONE	In vivo	Not mutagenic
CYCLOHEXANONE	In Vitro	Some positive data exist, but the data are not
		sufficient for classification

**Page** 10 **of** 16

ETHYL 3-ETHOXYPROPIONATE	In Vitro	Not mutagenic
EPOXIDIZED SOYBEAN OIL	In Vitro	Not mutagenic
Silica	In Vitro	Not mutagenic
ALUMINUM OXIDE	In Vitro	Not mutagenic
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-	In Vitro	Not mutagenic
dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-		
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-	In vivo	Not mutagenic
dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-		
Polymeric Benzotriazole	In Vitro	Not mutagenic
Polymeric Benzotriazole	In vivo	Not mutagenic
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	In Vitro	Not mutagenic
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	In vivo	Not mutagenic
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Titanium Dioxide	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
Titanium Dioxide	Inhalation	Rat	Carcinogenic
CYCLOHEXANONE	Ingestion	Multiple	Some positive data exist, but the data are not
		animal	sufficient for classification
		species	
EPOXIDIZED SOYBEAN OIL	Ingestion	Rat	Not carcinogenic
Silica	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification
ALUMINUM OXIDE	Inhalation	Rat	Not carcinogenic
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Not	Not	Carcinogenic
	Specified	applicabl	
		e	
Naphthalene	Inhalation	Multiple	Carcinogenic
		animal	
		species	

# **Reproductive Toxicity**

**Reproductive and/or Developmental Effects** 

Name	Route	Value	Species	Test Result	Exposure Duration
CYCLOHEXANONE	Inhalation	Not classified for female reproduction	Rat	NOAEL 4 mg/l	2 generation
CYCLOHEXANONE	Inhalation	Not classified for male reproduction	Rat	NOAEL 2 mg/l	2 generation
CYCLOHEXANONE	Ingestion	Not classified for development	Mouse	LOAEL 1,100 mg/kg/day	during organogenesi s
CYCLOHEXANONE	Inhalation	Not classified for development	Rat	NOAEL 2 mg/l	2 generation
EPOXIDIZED SOYBEAN OIL	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
EPOXIDIZED SOYBEAN OIL	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
EPOXIDIZED SOYBEAN OIL	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	1 generation
Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	Ingestion	Not classified for female reproduction	Rat	NOAEL 100 mg/kg/day	premating into lactation

Page 11 of

Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	Ingestion	Not classified for male reproduction	Rat	NOAEL 100 mg/kg/day	115 days
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-	Ingestion	Not classified for development	Rat	NOAEL 2 mg/kg/day	premating into lactation
Polymeric Benzotriazole	Ingestion	Not classified for female reproduction	Rat	NOAEL 100 mg/kg/day	premating into lactation
Polymeric Benzotriazole	Ingestion	Not classified for male reproduction	Rat	NOAEL 100 mg/kg/day	115 days
Polymeric Benzotriazole	Ingestion	Not classified for development	Rat	NOAEL 2 mg/kg/day	premating into lactation
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Not Specified	Not classified for female reproduction	Rat	NOAEL Not available	2 generation
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Not Specified	Not classified for male reproduction	Rat	NOAEL Not available	2 generation
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Not Specified	Not classified for development	Rat	NOAEL Not available	2 generation
ZINC 2-ETHYLHEXANOATE	Ingestion	Toxic to female reproduction	Rat	NOAEL 300 mg/kg/day	1 generation
ZINC 2-ETHYLHEXANOATE	Ingestion	Toxic to male reproduction	Rat	NOAEL 300 mg/kg/day	1 generation
ZINC 2-ETHYLHEXANOATE	Ingestion	Toxic to development	Rat	NOAEL 100 mg/kg/day	1 generation

# Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
CYCLOHEXANONE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Guinea pig	LOAEL 16.1 mg/l	6 hours
CYCLOHEXANONE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
CYCLOHEXANONE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
2-BUTOXYETHYL ACETATE	Dermal	blood	Not classified	similar compoun ds	NOAEL Not available	
2-BUTOXYETHYL ACETATE	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	similar compoun ds	NOAEL Not available	
2-BUTOXYETHYL ACETATE	Inhalation	blood	Not classified	similar compoun ds	NOAEL Not available	
2-BUTOXYETHYL ACETATE	Ingestion	blood	Not classified	similar compoun ds	NOAEL Not available	
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
ZINC 2- ETHYLHEXANOATE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
Naphthalene	Ingestion	blood	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the	Rat	LOAEL 0.01	2 years

**Page** 12 **of** 16

			data are not sufficient for classification		mg/l	
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
CYCLOHEXANONE	Inhalation	liver   kidney and/or bladder	Not classified	Rabbit	NOAEL 0.76 mg/l	50 days
CYCLOHEXANONE	Ingestion	liver	Not classified	Mouse	NOAEL 4,800 mg/kg/day	90 days
ETHYL 3- ETHOXYPROPIONATE	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	90 days
ETHYL 3- ETHOXYPROPIONATE	Inhalation	nervous system   heart   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 6 mg/l	17 days
ETHYL 3- ETHOXYPROPIONATE	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	17 days
ETHYL 3- ETHOXYPROPIONATE	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
ETHYL 3- ETHOXYPROPIONATE	Ingestion	kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	17 days
2-BUTOXYETHYL ACETATE	Dermal	blood	Not classified	similar compoun ds	NOAEL Not available	not available
2-BUTOXYETHYL ACETATE	Inhalation	blood	Not classified	similar compoun ds	NOAEL Not available	6 months
2-BUTOXYETHYL ACETATE	Ingestion	blood	Not classified	similar compoun ds	NOAEL Not available	13 weeks
EPOXIDIZED SOYBEAN OIL	Ingestion	liver   kidney and/or bladder	Not classified	Rat	NOAEL 1,250 mg/kg/day	2 years
Silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
ALUMINUM OXIDE	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
ALUMINUM OXIDE	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Poly(oxy-1,2- ethanediyl), .alpha[3-[3- (2H-benzotriazol-2-yl)-5- (1,1-dimethylethyl)-4- hydroxyphenyl]-1- oxopropyl]omega hydroxy-	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL not available	28 days
Poly(oxy-1,2- ethanediyl), .alpha[3-[3- (2H-benzotriazol-2-yl)-5- (1,1-dimethylethyl)-4- hydroxyphenyl]-1- oxopropyl]omega hydroxy-	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 50 mg/kg/day	90 days
Poly(oxy-1,2- ethanediyl), .alpha[3-[3- (2H-benzotriazol-2-yl)-5- (1,1-dimethylethyl)-4- hydroxyphenyl]-1- oxopropyl]omega hydroxy-	Ingestion	liver	Not classified	Rat	NOAEL 10 mg/kg/day	28 days
Poly(oxy-1,2- ethanediyl), .alpha[3-[3- (2H-benzotriazol-2-yl)-5-	Ingestion	eyes	Not classified	Rat	NOAEL 50 mg/kg/day	90 days

**Page** 13 **of** 16

(1,1-dimethylethyl)-4- hydroxyphenyl]-1- oxopropyl]omega hydroxy-						
Polymeric Benzotriazole	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL not available	28 days
Polymeric Benzotriazole	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 50 mg/kg/day	90 days
Polymeric Benzotriazole	Ingestion	liver	Not classified	Rat	NOAEL 10 mg/kg/day	28 days
Polymeric Benzotriazole	Ingestion	eyes	Not classified	Rat	NOAEL 50 mg/kg/day	90 days
Naphthalene	Dermal	blood	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Naphthalene	Dermal	eyes	Not classified	Human	NOAEL Not available	occupational exposure
Naphthalene	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.01 mg/l	13 weeks
Naphthalene	Inhalation	blood	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Naphthalene	Inhalation	eyes	Not classified	Human	NOAEL Not available	occupational exposure
Naphthalene	Ingestion	blood	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Naphthalene	Ingestion	eyes	May cause damage to organs though prolonged or repeated exposure	Rabbit	LOAEL 500 mg/kg/day	15 days

**Aspiration Hazard** 

Name	Value
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

#### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

# 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable), D043 (Vinyl chloride)

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501

# **SECTION 15: Regulatory information**

# 15.1. US Federal Regulations

Contact 3M for more information.

#### **EPCRA 311/312 Hazard Classifications:**

### Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

### **Health Hazards**

Carcinogenicity

Reproductive toxicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

### Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient C.A.S. No % by Wt

ALUMINUM OXIDE 1344-28-1 Trade Secret < 1.5

#### 15.2. State Regulations

Contact 3M for more information

#### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

# 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

### NFPA Hazard Classification

Health: 3 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

.....

 Document Group:
 25-1257-2
 Version Number:
 5.00

 Issue Date:
 05/19/21
 Supercedes Date:
 06/28/19

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com