



Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 18-4614-6 | Version Number: | 12.00 |
| Issue Date: | 07/02/19 | Supersedes Date: | 05/22/19 |

SECTION 1: Identification

1.1. Product identifier

3M™ Screen Print Matte Clear 1930

Product Identification Numbers

75-3470-5121-3, 75-3470-5122-1
7000130276, 7000056060

1.2. Recommended use and restrictions on use

Recommended use

Screen Print Clear Coat

1.3. Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Commercial Solutions Division |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Flammable Liquid: Category 4.
Skin Sensitizer: Category 1A.
Reproductive Toxicity: Category 1B.
Specific Target Organ Toxicity (repeated exposure): Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Combustible liquid.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure:
blood or blood-forming organs |

Precautionary Statements**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Keep container tightly closed.

Keep cool.

Store locked up in a well-ventilated place.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|--|---------------|------------------------|
| 2-BUTOXYETHYL ACETATE | 112-07-2 | 40 - 50 Trade Secret * |
| ETHYL 3-ETHOXYPROPIONATE | 763-69-9 | 10 - 20 Trade Secret * |
| ACRYLIC POLYMER | Trade Secret* | 10 - 20 Trade Secret * |
| POLYMERIC PLASTICIZER | Trade Secret* | 5 - 15 Trade Secret * |
| SILICA | 7631-86-9 | 5 - 10 Trade Secret * |
| VINYL ACETATE-VINYL ALCOHOL-VINYL CHLORIDE POLYMER | 25086-48-0 | 1 - 5 Trade Secret * |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | 64742-94-5 | < 1 Trade Secret * |

| | | |
|---|---------------|-------------------------|
| Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- | 104810-48-2 | 0.1 - 1 Trade Secret * |
| Polymeric Benzotriazole | 104810-47-1 | 0.1 - 1 Trade Secret * |
| Fluoroacrylate Copolymer | Trade Secret* | < 1 Trade Secret * |
| 2-Butoxyethanol | 111-76-2 | < 0.5 Trade Secret * |
| Methyl Methacrylate | 80-62-6 | 0 - 0.29 Trade Secret * |
| Toluene | 108-88-3 | 0 - 0.29 Trade Secret * |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate | 41556-26-7 | 0 - 0.1 Trade Secret * |
| ETHYL ACRYLATE | 140-88-5 | < 0.1 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Hydrogen Chloride
Oxides of Nitrogen

Condition

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|-----------------|------------|--------|--------------------------|--------------------------------|
| Toluene | 108-88-3 | ACGIH | TWA:20 ppm | A4: Not class. as human carcin |
| Toluene | 108-88-3 | OSHA | TWA:200 ppm;CEIL:300 ppm | |
| 2-Butoxyethanol | 111-76-2 | ACGIH | TWA:20 ppm | A3: Confirmed animal carcin. |

| | | | | |
|-----------------------|-----------|-------|--|---|
| 2-Butoxyethanol | 111-76-2 | OSHA | TWA:240 mg/m3(50 ppm) | SKIN |
| 2-BUTOXYETHYL ACETATE | 112-07-2 | ACGIH | TWA:20 ppm | A3: Confirmed animal carcin. |
| ETHYL ACRYLATE | 140-88-5 | ACGIH | TWA:5 ppm;STEL:15 ppm | A4: Not class. as human carcin |
| ETHYL ACRYLATE | 140-88-5 | OSHA | TWA:100 mg/m3(25 ppm) | SKIN |
| SILICA, AMORPHOUS | 7631-86-9 | OSHA | TWA concentration:0.8 mg/m3;TWA:20 millions of particles/cu. ft. | |
| Methyl Methacrylate | 80-62-6 | ACGIH | TWA:50 ppm;STEL:100 ppm | Dermal Sensitizer, A4: Not class. as human carcin |
| Methyl Methacrylate | 80-62-6 | OSHA | TWA:410 mg/m3(100 ppm) | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|---|
| General Physical Form: | Liquid |
| Specific Physical Form: | Liquid |
| Odor, Color, Grade: | Solvent Odor, Clear Color |
| Odor threshold | <i>No Data Available</i> |
| pH | <i>Not Applicable</i> |
| Melting point | <i>Not Applicable</i> |
| Boiling Point | >=329 °F |
| Flash Point | 150 °F [<i>Test Method:Closed Cup</i>] |
| Evaporation rate | <i>No Data Available</i> |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | 0.5 % |
| Flammable Limits(UEL) | 8.7 % |
| Vapor Pressure | <=1 mmHg [<i>@ 20 °C</i>] |
| Vapor Density | > 1 [<i>Ref Std:AIR=1</i>] |
| Density | 0.95 g/ml |
| Specific Gravity | 0.95 [<i>Ref Std:WATER=1</i>] |
| Solubility in Water | Moderate |
| Solubility- non-water | <i>No Data Available</i> |
| Partition coefficient: n-octanol/ water | <i>No Data Available</i> |
| Autoignition temperature | > 645 °F |
| Decomposition temperature | <i>No Data Available</i> |
| Viscosity | 7,000 - 8,000 centipoise |
| Volatile Organic Compounds | 681 [<i>Details:After maximum thinning</i>] |
| Volatile Organic Compounds | 573 [<i>Details:As manufactured</i>] |
| Percent volatile | 50 - 60 % |
| VOC Less H2O & Exempt Solvents | 573 g/l [<i>Details:As manufactured</i>] |
| VOC Less H2O & Exempt Solvents | 681 [<i>Details:After maximum thinning</i>] |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled.

May cause additional health effects (see below).

Skin Contact:

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Blood Effects: Signs/symptoms may include generalized weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and/or hemoglobinemia.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

| Ingredient | CAS No. | Class Description | Regulation |
|----------------|----------|-------------------------------|---|
| ETHYL ACRYLATE | 140-88-5 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|-----------------------|------------------------|-------------------------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE ₂₀ - 50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE _{2,000} - 5,000 mg/kg |
| 2-BUTOXYETHYL ACETATE | Inhalation-Vapor | official classification | LC ₅₀ estimated to be 10 - 20 mg/l |

| | | | |
|---|--------------------------------|------------|--|
| 2-BUTOXYETHYL ACETATE | Dermal | Rabbit | LD50 > 4,766 mg/kg |
| 2-BUTOXYETHYL ACETATE | Ingestion | Rat | LD50 2,400 mg/kg |
| ETHYL 3-ETHOXYPROPIONATE | Dermal | Rabbit | LD50 4,080 mg/kg |
| ETHYL 3-ETHOXYPROPIONATE | Inhalation-Vapor (4 hours) | Rat | LC50 > 14.4 mg/l |
| ETHYL 3-ETHOXYPROPIONATE | Ingestion | Rat | LD50 3,200 mg/kg |
| SILICA | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| SILICA | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| SILICA | Ingestion | Rat | LD50 > 5,110 mg/kg |
| VINYL ACETATE-VINYL ALCOHOL-VINYL CHLORIDE POLYMER | Dermal | Rabbit | LD50 > 8,000 mg/kg |
| VINYL ACETATE-VINYL ALCOHOL-VINYL CHLORIDE POLYMER | Ingestion | Rat | LD50 > 8,000 mg/kg |
| Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- | Dermal | Rat | LD50 > 2,000 mg/kg |
| Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 5.8 mg/l |
| Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Polymeric Benzotriazole | Dermal | Rat | LD50 > 2,000 mg/kg |
| Polymeric Benzotriazole | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 5.8 mg/l |
| Polymeric Benzotriazole | Ingestion | Rat | LD50 > 5,000 mg/kg |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Ingestion | Rat | LD50 > 5,000 mg/kg |
| 2-Butoxyethanol | Dermal | Guinea pig | LD50 > 2,000 mg/kg |
| 2-Butoxyethanol | Inhalation-Vapor (4 hours) | Guinea pig | LC50 > 2.6 mg/l |
| 2-Butoxyethanol | Ingestion | Guinea pig | LD50 1,414 mg/kg |
| Toluene | Dermal | Rat | LD50 12,000 mg/kg |
| Toluene | Inhalation-Vapor (4 hours) | Rat | LC50 30 mg/l |
| Toluene | Ingestion | Rat | LD50 5,550 mg/kg |
| Methyl Methacrylate | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Methyl Methacrylate | Inhalation-Vapor (4 hours) | Rat | LC50 29 mg/l |
| Methyl Methacrylate | Ingestion | Rat | LD50 7,900 mg/kg |
| Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate | Dermal | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate | Ingestion | Rat | LD50 3,125 mg/kg |
| ETHYL ACRYLATE | Dermal | Rabbit | LD50 1,790 mg/kg |
| ETHYL ACRYLATE | Inhalation-Vapor (4 hours) | Rat | LC50 9 mg/l |
| ETHYL ACRYLATE | Ingestion | Rat | LD50 1,020 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|-----------|---------------------------|
| 2-BUTOXYETHYL ACETATE | Rabbit | Minimal irritation |
| ETHYL 3-ETHOXYPROPIONATE | Rabbit | No significant irritation |
| SILICA | Rabbit | No significant irritation |
| VINYL ACETATE-VINYL ALCOHOL-VINYL CHLORIDE POLYMER | Professio | No significant irritation |

| | nal judgeme nt | |
|---|------------------------|---------------------------|
| Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- | Rabbit | No significant irritation |
| Polymeric Benzotriazole | Rabbit | No significant irritation |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Rabbit | Irritant |
| 2-Butoxyethanol | Rabbit | Irritant |
| Toluene | Rabbit | Irritant |
| Methyl Methacrylate | Human and animal | Mild irritant |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny)l) sebacate | Rabbit | No significant irritation |
| ETHYL ACRYLATE | Rabbit | Corrosive |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|----------------------------------|---------------------------|
| 2-BUTOXYETHYL ACETATE | Rabbit | Mild irritant |
| ETHYL 3-ETHOXYPROPIONATE | Rabbit | Mild irritant |
| SILICA | Rabbit | No significant irritation |
| VINYL ACETATE-VINYL ALCOHOL-VINYL CHLORIDE POLYMER | Professo nal judgeme nt | No significant irritation |
| Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- | Rabbit | No significant irritation |
| Polymeric Benzotriazole | Rabbit | No significant irritation |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Rabbit | Mild irritant |
| 2-Butoxyethanol | Rabbit | Severe irritant |
| Toluene | Rabbit | Moderate irritant |
| Methyl Methacrylate | Rabbit | Moderate irritant |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny)l) sebacate | Rabbit | No significant irritation |
| ETHYL ACRYLATE | Rabbit | Corrosive |

Skin Sensitization

| Name | Species | Value |
|---|------------------------|----------------|
| ETHYL 3-ETHOXYPROPIONATE | Guinea pig | Not classified |
| SILICA | Human and animal | Not classified |
| Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- | Guinea pig | Sensitizing |
| Polymeric Benzotriazole | Guinea pig | Sensitizing |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Guinea pig | Not classified |
| 2-Butoxyethanol | Guinea pig | Not classified |
| Toluene | Guinea pig | Not classified |
| Methyl Methacrylate | Human and animal | Sensitizing |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny)l) sebacate | Guinea pig | Sensitizing |
| ETHYL ACRYLATE | Human and animal | Sensitizing |

Respiratory Sensitization

| Name | Species | Value |
|------|---------|-------|
| | | |

| | | |
|---------------------|-------|----------------|
| Methyl Methacrylate | Human | Not classified |
|---------------------|-------|----------------|

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|--|
| ETHYL 3-ETHOXYPROPIONATE | In Vitro | Not mutagenic |
| SILICA | In Vitro | Not mutagenic |
| 2-Butoxyethanol | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Toluene | In Vitro | Not mutagenic |
| Toluene | In vivo | Not mutagenic |
| Methyl Methacrylate | In vivo | Not mutagenic |
| Methyl Methacrylate | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|--|---------------|-------------------------|--|
| SILICA | Not Specified | Mouse | Some positive data exist, but the data are not sufficient for classification |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| 2-Butoxyethanol | Inhalation | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |
| Toluene | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Toluene | Ingestion | Rat | Some positive data exist, but the data are not sufficient for classification |
| Toluene | Inhalation | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Methyl Methacrylate | Ingestion | Rat | Not carcinogenic |
| Methyl Methacrylate | Inhalation | Human and animal | Not carcinogenic |
| ETHYL ACRYLATE | Ingestion | Multiple animal species | Carcinogenic |

Reproductive Toxicity**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test Result | Exposure Duration |
|-----------------|------------|--|-------------------------|-----------------------|-----------------------|
| SILICA | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| SILICA | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| SILICA | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesis |
| 2-Butoxyethanol | Dermal | Not classified for development | Rat | NOAEL 1,760 mg/kg/day | during gestation |
| 2-Butoxyethanol | Ingestion | Not classified for development | Rat | NOAEL 100 mg/kg/day | during organogenesis |
| 2-Butoxyethanol | Inhalation | Not classified for development | Multiple animal species | NOAEL 0.48 mg/l | during organogenesis |
| Toluene | Inhalation | Not classified for female reproduction | Human | NOAEL Not available | occupational exposure |
| Toluene | Inhalation | Not classified for male reproduction | Rat | NOAEL 2.3 mg/l | 1 generation |
| Toluene | Ingestion | Toxic to development | Rat | LOAEL 520 | during |

| | | | | mg/kg/day | gestation |
|---------------------|------------|--------------------------------------|-------|---------------------|------------------------|
| Toluene | Inhalation | Toxic to development | Human | NOAEL Not available | poisoning and/or abuse |
| Methyl Methacrylate | Inhalation | Not classified for male reproduction | Mouse | NOAEL 36.9 mg/l | |
| Methyl Methacrylate | Inhalation | Not classified for development | Rat | NOAEL 8.3 mg/l | during organogenesis |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--|------------|---|--|-------------------------|---------------------|-------------------|
| 2-BUTOXYETHYL ACETATE | Dermal | kidney and/or bladder | Not classified | Rabbit | NOAEL Not available | 24 hours |
| 2-BUTOXYETHYL ACETATE | Dermal | blood | Not classified | Rabbit | LOAEL 3,191 mg/kg | 24 hours |
| 2-BUTOXYETHYL ACETATE | Dermal | heart endocrine system hematopoietic system liver nervous system | Not classified | Rabbit | NOAEL 10,000 mg/kg | 24 hours |
| 2-BUTOXYETHYL ACETATE | Inhalation | central nervous system depression | Some positive data exist, but the data are not sufficient for classification | similar compounds | NOAEL Not available | |
| 2-BUTOXYETHYL ACETATE | Inhalation | blood heart endocrine system hematopoietic system liver nervous system kidney and/or bladder respiratory system | Not classified | Multiple animal species | NOAEL 2.6 mg/l | 4 hours |
| 2-BUTOXYETHYL ACETATE | Ingestion | blood | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 2,400 mg/kg | not applicable |
| 2-BUTOXYETHYL ACETATE | Ingestion | hematopoietic system | Not classified | Rat | NOAEL 2,400 mg/kg | not applicable |
| 2-BUTOXYETHYL ACETATE | Ingestion | kidney and/or bladder | Not classified | Rat | LOAEL 2,400 mg/kg | not applicable |
| 2-BUTOXYETHYL ACETATE | Ingestion | heart liver nervous system | Not classified | Rat | NOAEL 3,000 mg/kg | not applicable |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Professional judgment | NOAEL Not available | |
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professional judgment | NOAEL Not available | |
| 2-Butoxyethanol | Dermal | endocrine system | Not classified | Rabbit | NOAEL 902 mg/kg | 6 hours |
| 2-Butoxyethanol | Dermal | liver | Not classified | Rabbit | LOAEL 72 mg/kg | not available |
| 2-Butoxyethanol | Dermal | kidney and/or bladder | Not classified | Rabbit | LOAEL 451 mg/kg | 6 hours |
| 2-Butoxyethanol | Dermal | blood | Not classified | Multiple animal species | NOAEL Not available | |
| 2-Butoxyethanol | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| 2-Butoxyethanol | Inhalation | respiratory irritation | Some positive data exist, but the | Human | NOAEL Not | |

| | | | | | | |
|---------------------|------------|-----------------------------------|--|-------------------------|---------------------|------------------------|
| | | | data are not sufficient for classification | | available | |
| 2-Butoxyethanol | Inhalation | blood | Not classified | Multiple animal species | NOAEL Not available | |
| 2-Butoxyethanol | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professional judgement | NOAEL Not available | |
| 2-Butoxyethanol | Ingestion | blood | Not classified | Multiple animal species | NOAEL Not available | |
| 2-Butoxyethanol | Ingestion | kidney and/or bladder | Not classified | Human | NOAEL Not available | poisoning and/or abuse |
| Toluene | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Toluene | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Toluene | Inhalation | immune system | Not classified | Mouse | NOAEL 0.004 mg/l | 3 hours |
| Toluene | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | poisoning and/or abuse |
| Methyl Methacrylate | Inhalation | respiratory irritation | May cause respiratory irritation | Human | NOAEL Not available | occupational exposure |
| ETHYL ACRYLATE | Inhalation | respiratory irritation | May cause respiratory irritation | Multiple animal species | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--------------------------|------------|---|--|-------------------------|-----------------------|-----------------------|
| 2-BUTOXYETHYL ACETATE | Inhalation | blood | May cause damage to organs though prolonged or repeated exposure | Multiple animal species | NOAEL 0.7 mg/l | 10 months |
| 2-BUTOXYETHYL ACETATE | Inhalation | kidney and/or bladder | Not classified | Multiple animal species | LOAEL 0.7 mg/l | 10 months |
| 2-BUTOXYETHYL ACETATE | Inhalation | heart endocrine system hematopoietic system liver nervous system respiratory system | Not classified | Multiple animal species | NOAEL 0.7 mg/l | 10 months |
| ETHYL 3-ETHOXYPROPIONATE | Inhalation | hematopoietic system | Not classified | Rat | NOAEL 6 mg/l | 90 days |
| ETHYL 3-ETHOXYPROPIONATE | Inhalation | nervous system heart liver immune system kidney and/or bladder | Not classified | Rat | NOAEL 6 mg/l | 17 days |
| ETHYL 3-ETHOXYPROPIONATE | Ingestion | liver | Not classified | Rat | NOAEL 1,000 mg/kg/day | 17 days |
| ETHYL 3-ETHOXYPROPIONATE | Ingestion | hematopoietic system | Not classified | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| ETHYL 3-ETHOXYPROPIONATE | Ingestion | kidney and/or bladder respiratory system | Not classified | Rat | NOAEL 1,000 mg/kg/day | 17 days |
| SILICA | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| 2-Butoxyethanol | Dermal | blood | Not classified | Multiple animal species | NOAEL Not available | not available |
| 2-Butoxyethanol | Dermal | endocrine system | Not classified | Rabbit | NOAEL 150 mg/kg/day | 90 days |

| | | | | | | |
|---------------------|------------|---|--|-------------------------|-----------------------|------------------------|
| 2-Butoxyethanol | Inhalation | liver | Not classified | Rat | NOAEL 2.4 mg/l | 14 weeks |
| 2-Butoxyethanol | Inhalation | kidney and/or bladder | Not classified | Rat | NOAEL 0.15 mg/l | 14 weeks |
| 2-Butoxyethanol | Inhalation | blood | Not classified | Rat | LOAEL 0.15 mg/l | 6 months |
| 2-Butoxyethanol | Inhalation | endocrine system | Not classified | Dog | LOAEL 1.9 mg/l | 8 days |
| 2-Butoxyethanol | Ingestion | blood | Not classified | Rat | LOAEL 69 mg/kg/day | 13 weeks |
| 2-Butoxyethanol | Ingestion | kidney and/or bladder | Not classified | Multiple animal species | NOAEL Not available | not available |
| Toluene | Inhalation | auditory system eyes olfactory system | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | poisoning and/or abuse |
| Toluene | Inhalation | nervous system | May cause damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | poisoning and/or abuse |
| Toluene | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 2.3 mg/l | 15 months |
| Toluene | Inhalation | heart liver kidney and/or bladder | Not classified | Rat | NOAEL 11.3 mg/l | 15 weeks |
| Toluene | Inhalation | endocrine system | Not classified | Rat | NOAEL 1.1 mg/l | 4 weeks |
| Toluene | Inhalation | immune system | Not classified | Mouse | NOAEL Not available | 20 days |
| Toluene | Inhalation | bone, teeth, nails, and/or hair | Not classified | Mouse | NOAEL 1.1 mg/l | 8 weeks |
| Toluene | Inhalation | hematopoietic system vascular system | Not classified | Human | NOAEL Not available | occupational exposure |
| Toluene | Inhalation | gastrointestinal tract | Not classified | Multiple animal species | NOAEL 11.3 mg/l | 15 weeks |
| Toluene | Ingestion | heart | Not classified | Rat | NOAEL 2,500 mg/kg/day | 13 weeks |
| Toluene | Ingestion | liver kidney and/or bladder | Not classified | Multiple animal species | NOAEL 2,500 mg/kg/day | 13 weeks |
| Toluene | Ingestion | hematopoietic system | Not classified | Mouse | NOAEL 600 mg/kg/day | 14 days |
| Toluene | Ingestion | endocrine system | Not classified | Mouse | NOAEL 105 mg/kg/day | 28 days |
| Toluene | Ingestion | immune system | Not classified | Mouse | NOAEL 105 mg/kg/day | 4 weeks |
| Methyl Methacrylate | Dermal | peripheral nervous system | Not classified | Human | NOAEL Not available | occupational exposure |
| Methyl Methacrylate | Inhalation | olfactory system | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |
| Methyl Methacrylate | Inhalation | kidney and/or bladder | Not classified | Multiple animal species | NOAEL Not available | 14 weeks |
| Methyl Methacrylate | Inhalation | liver | Not classified | Mouse | NOAEL 12.3 mg/l | 14 weeks |
| Methyl Methacrylate | Inhalation | respiratory system | Not classified | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

| Name | Value |
|--|-------------------|
| HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM) | Aspiration hazard |
| Toluene | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information

on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D018 (Benzene)

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

Health Hazards

Reproductive toxicity

Respiratory or Skin Sensitization

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient

2-BUTOXYETHYL ACETATE (GLYCOL
ETHERS)

C.A.S. No

112-07-2

% by Wt

40 - 50

2-Butoxyethanol (GLYCOL ETHERS)

111-76-2

< 0.5

This material contains a chemical which requires export notification under TSCA Section 12[b]:

Ingredient (Category if applicable)

Fluoroacrylate Copolymer

C.A.S. No

Trade Secret

RegulationToxic Substances Control Act (TSCA) 5
SNUR or Consent Order Chemicals**Status**

Applicable

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information**NFPA Hazard Classification****Health: 2 Flammability: 2 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 18-4614-6**Version Number:** 12.00**Issue Date:** 07/02/19**Supersedes Date:** 05/22/19

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com