



# Conversion Guide for 3M™ Secure Click™ Half Facepiece HF-800 Series and Full Facepiece FF-800 Series

Designed with smart and intuitive features, the 3M Secure Click HF-800 and FF-800 help protect workers from particulates and a wide variety of gases and vapors when used with approved 3M Secure Click filters and cartridges shown below.



If you are currently using a 3M respirator with a bayonet connection, this guide will offer conversion suggestions to help you transition to 3M Secure Click.





## Gas and Vapor Cartridges

|  |  |
|--|--|
|  |  |
| <b>Bayonet Connection</b>  | <b>3M™ Secure Click™</b>   |
| 6001 OV  | D8001 OV   |
| 6002 AG  | D8002 AG   |
| 6003 OV/AG   | D8003 OV/AG  |
| 6004 AM/ME   | D8004 AM/ME  |
| 6005 FM/OV   | D8005 FM/OV  |
| 6006 MG/V  | D8006 MG/V   |
| 6007 MV/OV/AG  | D8009 MV/MG  |



## Combination Gas & Vapor Cartridges

|  |  |
|--|--|
|  |  |
| <b>Bayonet Connection</b>  | <b>3M™ Secure Click™</b>   |
| 60921 OV/P100  | D80921 OV/P100   |
| 60923 OV/AG/P100   | D80923 OV/AG/P100  |
| 60926 MG/V/P100  | D80926 MG/V/P100   |
| 60927 MV/OV/AG/P100  | D80929 MV/MG/P100  |

## P95 Particulate Filters

|   |   |
|---|---|
|  |  |
| <b>Bayonet Connection</b>   | <b>3M™ Secure Click™</b>  |
| 2071  | D3071   |
| 2076HF*   | D3076HF*  |
| 2078**  | D3078**   |



## P100 Particulate Filters

|   |   |
|---|---|
|  |  |
| <b>Bayonet Connection</b>   | <b>3M™ Secure Click™</b>  |
| 2091  | D3091   |
| 2096*   | D3096*  |
| 2097***   | D3097***  |

## P100 Particulate Filters Continued

|   |   |
|---|---|
|  |  |
| <b>Bayonet Connection</b>   | <b>3M™ Secure Click™</b>  |
| 7093 / 7093B  | D9093 / D9093B  |
| 7093C** / 7093CB**  | D9093C** / D9093CB**  |

## Replaceable Particulate Filters & Retainer

|  |   |
|--|---|
|  |  |
| <b>Bayonet Connection</b>  | <b>3M™ Secure Click™</b>  |
| 5N11 N95   | D7N11 N95   |
| 5P71 P95   | D7P71 P95   |
| 501 Filter Retainer  | D701 Filter Retainer  |

Nuisance level refers to concentrations less than the OSHA PEL or applicable government occupational exposure limits, whichever is lower.

\* 3M recommended for relief against nuisance levels of acid gases.

\*\* 3M recommended for relief against nuisance levels of organic vapor/acid gases.

\*\*\* 3M recommended for relief against nuisance levels of organic vapors. 3M recommended for use against up to 1 ppm ozone for up to 8 hours. Not NIOSH approved for use against ozone.




Personal Safety Division  
3M Center, Building 223-4S-02  
St. Paul, MN 55144-1000

Phone 1-800-328-1667  
Web [www.3M.com/reusable](http://www.3M.com/reusable)

For respiratory training and advice please contact your local 3M representative.

3M is a trademark of 3M Company. Please recycle.  
© 3M 2024. All rights reserved.  
70-0717-3944-8



**⚠WARNING**  
These respirators help protect against certain airborne contaminants. Before use, the wearer must read and understand the User Instructions provided as a part of the product packaging. A written respiratory protection program must be implemented meeting all the requirements of OSHA 1910.134 including training, fit testing and medical evaluation. In Canada, CSA standards Z94.4 requirements must be met and/or requirements of the applicable jurisdiction, as appropriate. Misuse may result in sickness or death. For correct use, see supervisor and User Instructions, or call 3M PSD Technical Service in USA at 1-800-243-4630 and in Canada at 1-800-267-4414.