

3M™ UV Resistant Green Masking Tape

Designed for UV resistance and clean removal.

Created for ultraviolet (UV) light resistance, 3M™ UV Resistant Green Masking Tape is an excellent choice for indoor and outdoor bundling, holding, sealing, paint masking and surface protection. The tape removes cleanly from most surfaces with little to no edge residue for up to 14 days even after outdoor exposure. It adheres to a variety of substrates and withstands temperatures up to 175°F (79°C) for up to 30 minutes. With easy unwind and hand tearability, this cost-effective solution will come in handy for a wide variety of both indoor and outdoor masking applications.



UV resistance

UV resistant crepe paper tape maintains performance for up to 14 days outdoors.



Clean removal

Removes cleanly from most surfaces with little to no edge residue for up to 14 days.



Professional paint lines

Consistently delivers crisp paint lines, even after outdoor exposure.



Holding power

Adheres to a variety of substrates and conforms to irregular surfaces.



Versatile UV performance for indoor and outdoor masking.



3M™ UV Resistant Green Masking Tape offers 14 days of UV resistance without compromising on holding power or paint line quality. For more information on 3M Masking Solutions, contact your local 3M representative, call 1-800-362-3550 or visit [3M.com/masking](https://www.3m.com/masking).



Product	Material IDs	Width	Length	Rolls/Case
3M™ UV Resistant Green Masking Tape	7100299467	12 mm	55 m	96
	7100299468	18 mm	55 m	72
	7100299469	24 mm	55 m	48
	7100299470	36 mm	55 m	36
	7100299471	48 mm	55 m	24
	7100299472	72 mm	55 m	24
	7100299473	96 mm	55 m	24

Specifications

Total Thickness: 4.8 mil (0.12 mm)

Adhesion to Steel: 25 oz/in (2.8 N/cm)

Tensile Strength: 18 lb/in (33 N/cm)

Elongation at Break: 15%



Closure and Masking Systems Division
 3M Center, Building 225-3S-06
 St. Paul, MN 55144-1000
 800-362-3550 877-369-2923 (Fax)
[3M.com/masking](https://www.3m.com/masking)

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for proper evaluation (including, but not limited to, fitness for purpose and suitability of application), selection, and use of 3M products. Safety products should always be selected and used in accordance with all applicable regulations and standards (e.g., OSHA, ANSI, and others), after conducting a proper hazard assessment. Failure to properly evaluate, select, and use a 3M product may result in injury, sickness, death, and/or harm to property. Dispose of used atomizing heads, residual paint/coatings, used containers/materials, and PPS in accordance with local regulations.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

3M is a trademark of 3M Company. Please recycle. Printed in USA.

© 3M 2023. All rights reserved. 70-0717-0975-5