## OTDC400US02



## Products + Low Voltage Products and Systems + Switches + DC Switch-Disconnectors

| General Information                                       |   |
|---|---|
| Extended Product Type:                                    | OTDC400US02   |
| Product ID:   | 1SCA132354R1001   |
| EAN:  | 6417019614885   |
| Catalog Description:                                      | OTDC400US02 PV Disconnect Switch  |
| Long Description:   | OTDC400US02 PV Disconnect Switch, Terminal bolt kit included, Handle a    |
|   | nd shaft need to be ordered separately, Base mounting, US single-wire bre |
|   | ak, UL 1000 VDC 400 A, IEC 1000 VDC 500 A                                 |
| Ordering  |   |
| Minimum Order Quantity:                                   | 1 piece   |
| Customs Tariff Number:                                    | 85365080  |
| Popular Downloads   |   |
| -   |   |
| Data Sheet, Technical Information                         |   |
| Instructions and Manuals:                                 | 1SCC301085M0203   |
| Dimensions  |   |
| Product Net Width:  | 197 mm  |
| Product Net Height:                                       | 227 mm  |
| Product Net Depth / Length:                               | 105 mm  |
| Product Net Weight:                                       | 3.93 kg   |
|   | 8.66 lb   |
| Technical   |   |
| Rated Operational Current DC-21E<br>(I <sub>e</sub> ):    | 3 (1000 V) 500 A  |
| Conventional Thermal Current                              | Fully Enclosed 500 A  |
| (I <sub>the</sub> ):                                      |   |
| Rated Impulse Withstand Voltage                           | 12 kV   |
| (U <sub>imp</sub> ):                                      |   |
| Rated Insulation Voltage (U <sub>i</sub> ):               | 1500 V  |
| Rated Operational Voltage:                                | 1000 V  |
| Rated Short-time Withstand<br>Current (I <sub>cw</sub> ): | for 1 s 10 kiloampere rms   |
| Power Loss:   | at Rated Operating Conditions per Pole 15 W                               |
| Pollution Degree:   | 3   |
|   |   |

| Handle Type:                     | Handle and shaft not included                        |
|----------------------------------|--|
| Switches Operating Mechanism:    | Mechanism at the End of the Switch<br>02 (Left Side) |
| Operating Mode:                  | Front Operated                                       |
| Standards:                       | IEC&UL   |
| Special Functions:               | US single-wire break                                 |
| Mounting Type:                   | Base mounting  |
| Number of Circuits:              | 1  |
| Number of Poles:                 | 2  |
| Degree of Protection:            | Front IP20   |
| Terminal Type:                   | Lug terminals  |
| Technical UL/CSA                 |  |
| Ampere Rating UL/CSA:            | 1000 VDC 400 A                                       |
| Certificates and Declarations (I | Document Number)                                     |
| Declaration of Conformity - CE:  | 1SCC301009K0201                                      |
| Instructions and Manuals:        | 1SCC301085M0203                                      |
| <b>RoHS Information:</b>         | 2009Q4   |
| Container Information            |  |
| Package Level 1 Units:           | 1 piece  |
| Package Level 1 Width:           | 243 mm<br>9.57 in                                    |
| Package Level 1 Depth / Length:  | 259 mm<br>10.2 in                                    |
| Package Level 1 Height:          | 143 mm<br>5.63 in                                    |
| Package Level 1 Gross Weight:    | 4.215 kg<br>9.29 lb                                  |
| Package Level 1 EAN:             | 6417019614885  |
| Classifications                  |  |
| Object Classification Code:      | Q  |
| ETIM 5:                          | EC000216 - Switch disconnector                       |
| ETIM 6:                          | EC000216 - Switch disconnector                       |
| ETIM 7:                          | EC000216 - Switch disconnector                       |

