

SPECIFICATION SHEET

44-3745

MAXICUT® ULTRA™ BY ATG®, PREMIUM BLUE ENGINEERED YARN SHELL, BLACK MICRO-FOAM NITRILE COATING

- Micro-Foam nitrile coatings are compatible with light oils and will provide a good grip and excellent abrasion resistance
- Unique high performance yarns and fibers that offer cut protection while maintaining high levels of comfort
- Reinforcement between the thumb and forefinger
- Patented micro-foam nitrile coating offers 360° breathability making it the most breathable cut resistant glove on the market
- Optimized grip delivered through our micro-cup finish
- Minimal penetration (strike through) leaving only the soft liner resting against the skin
- The Skin Health Alliance has awarded professional dermatological accreditation following review of the scientific dossier behind this product
- · Silicone free
- Complies with FDA food handling requirements (21 CFR 177.2600)
- This style is also available tri-folded and shrink-wrapped for carefree dispensing through vending machines (44-3745V)
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves

APPLICATIONS

- · DIY and Gardening
- Finishing and inspection
- · Handling of small components
- Primary, secondary and final assembly
- Maintenance
- · Logistics and warehousing
- Using tools and instruments

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C)

TECHNICAL DATA

MATERIAL	Seamless knit engineered yarn, micro-foam nitrile coating						
COLOR	■ Blue/ Black						
CUFF STYLE	Continuous Knit XS - XXXL						
SIZES							
PACKAGING	12 per dozen, 6 dozen per case						
CASE	19.7" x 11.6" x 7.9" / 50cm x 29.5cm x 20cm						
CASE	XS	S	M	L	XL	XXL	XXXL
WEIGHT	8.8 lbs 4 kg	9.9 lbs 4.5 kg	10.5 lbs 4.75 kg	11 lbs 5 kg	11.9 lbs 5.4 kg	12.5 lbs 5.65 kg	12.8 lbs 5.8 kg
C00	Sri Lanka						

PERFORMANCE PROPERTIES

EN388: 4542	ASTM F2992-15 ANSI Cut Level A3 (Adopted by ANSI/ISEA 02/16) ASTM F1790-05 ANSI Cut Level 3					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5













BARCODES

ITEM	PAIR	DOZEN	CASE	
44-3745/XS	616314178528	01616314178527	02616314178526	
44-3745/S	616314178504	01616314178503	02616314178502	
44-3745/M	616314178498	01616314178497	02616314178496	
44-3745/L	616314178481	01616314178480	02616314178489	
44-3745/XL	616314178511	01616314178510	02616314178519	
44-3745/XXL	616314178535	01616314178534	02616314178533	
44-3745/XXXL	616314178542	01616314178541	02616314178540	

DIMENSIONS (in/cm)

		XS		M		XL	XXL	XXXL
	A	7.87 / 20	8.27 / 21	8.66 / 22	9.6 / 23	9.45 / 24	9.65 / 24.5	9.65 / 24.5
I	В	3.2 / 8.2	3.4 / 8.6	3.8 / 9.6	3.9 / 9.8	3.9 / 10	4.0 / 10.2	4.1 / 10.4
ı	Н	Blue	☐ White	Green	Brown	Yellow	■ Gray	Purple

