

Portable Mancoolers

Direct Drive Models 115V



4-IN-1 Fan

Features/Specifications:

- 2 year warranty
- Tilttable
- One fan, four mounting options
- All mountings in one box
- Easy to assemble
- Guards, Barrel, Mountings epoxy coated
- Pull Chain Switch



Performance:

Prop Dia.	Fan Style	CFM	RPM	F.L. Amps
30"	4-IN-1 All Mounts	5670 / 4590 / 3410	1110 / 810 / 600	2.9 / 2.1 / 1.93
36"	4-IN-1 All Mounts	11200 / 8090	830 / 600	4.6 / 3.5

Information:

EDP #	Catalog No.	Prop Dia.	Fan Style	HP	Ship Wt.
60470	DD3041	30"	4-IN-1 All Mounts	1/4	97
60471	DD3641	36"	4-IN-1 All Mounts	1/2	119

A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions.

24" Mancooler

Features/Specifications:

- 2 year warranty
- Tilttable
- Ball bearing motor
- Two speed rocker switch
- Epoxy coated barrel
- Epoxy coated steel spiral resilient mounted guards
- Handle with cord wrap for 10' cord with three prong plug
- 1/4 HP, 1 Phase, Totally Enclosed Air Over



Information:

EDP #	Catalog No.	Prop Dia.	Fan Style	HP	CFM High Low	RPM High Low	Amps	Ship Wt.
70001	DDMC24C	24"	Portable Barrel	1/4	4000 / 2100	1100 / 800	3.5	75



Ordering:

Fan No.	EDP #	Qty.	Catalog No.	Comments

Project		Location	
Engineer		Contractor	

Submitted by		Date		Approved by		Date	
--------------	--	------	--	-------------	--	------	--