

SPECIFICATION SHEET 48-L162Y



ASSURANCE® UNSUPPORTED LATEX, FLOCK LINED WITH RAISED DIAMOND GRIP - 16 MIL

- Provides resistance to acids, alkalis, alcohols, salts, ketones, and animals fats
- · Flock lining provides increased comfort and ease of donning
- Raised Diamond pattern for an enhanced grip
- Pinked zig-zag cuff for tear resistance
- · Pair packed for ease of distribution
- Made from component materials which comply with FDA regulations for food contact, 21CFR 177.2600
- Silicone Free

APPLICATIONS

- Janitorial
- Sanitation
- General maintenance

CARE INSTRUCTIONS

It is strongly advised to not wash and re-use these gloves when they are used to protect against chemical products

TECHNICAL DATA

MATERIAL	Natural rubber latex	
COLOR	Yellow	
CUFF STYLE	Zig-zag cuff	
SIZES	S - XL	
PACKAGING	1 pair per bag, 12 pair per pack, 12 dozen per case	
CASE	12.6" x 10.9" x 12.5" / 32cm x 27.6cm x 31.8cm	
CASE WEIGHT	17.6 lbs / 3.7 kg	
C00	Malaysia	

PERFORMANCE PROPERTIES

EN388: 1010						
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5

ELONGATION INFORMATION

BEFORE	AGING	AFTER ACCELERATED AGING		
Tensile Strength (minimum)	Tensile Strength Elongation (minimum)		Elongation (minimum)	
(Mpa)	%	(Mpa)	%	
10	500	75	375	



BARCODES

ITEM	PAIR	DOZEN	CASE
48-L162Y/XL	616314035159	01616314035159	02616314035159
48-L162Y/L	616314035128	01616314035128	02616314035128
48-L162Y/M	616314035135	01616314035135	02616314035135
48-L162Y/S	616314035142	01616314035142	02616314035142

DIMENSIONS (in/cm)

		M		XL		
Α	12.0 / 30.5	12.0 / 30.5	12.0 / 30.5	12.0 / 30.5		
В	3.5 / 9.0	3.9 / 10.0	4.3 / 10.8	4.6 / 11.6		
	Palm Thickness: 0.40mm					
	Cuff Thickness: 0.35mm					
	Finger Tip Thickness: 0.43mm					

