


Bondhus Ball End tools feature unrivaled precision machining



All Bondhus Ball End tools feature a precise 25° working angle



25° working angle allows tool to work in hard to reach places

www.bondhus.com



High Torque Steel:

Up to 20% stronger, with more torque and twice the wear resistance of standard grades of steel.



Durable color-coded finish for superior protection and easy tool identification.









Sets

| Sets | PART# | MODEL# I | PCS | LENGTH | CONTENTS | QTY |
|--------|----------------|----------------------|-----|--------------------|--|-----|
| Inch | 69637 | BLX13XLCG | 13 | Extra Long | .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4, 5/16, 3/8" | 1 |
| Metric | 69699 69499 | BLX9MXLCG BLX9MCG | 9 | Extra Long Long | 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10mm 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10mm | 1 |

Multi Packs

| PART# | MODEL# | PCS | LENGTH | CONTENTS | QTY |
|-------|-----------|-----|------------|--------------------------------------|-----|
| 69600 | BLX22XLCG | 22 | Extra Long | 69637 (.050-3/8") + 69699 (1.5-10mm) | 1 |





Bondhus Corporation 1400 E Broadway • PO Box 660 • Monticello, MN 55362 Tel: 763-295-2162 • Toll Free: 800-328-8310 • Fax: 763-295-4440

Bondhus, Protanium, and ColorGuard are trademarks of Bondhus Corporation.

Distributed by: