



## Power Lube® Industrial High Performance Lubricant w/PTFE, 11 Wt Oz

No. 03045 | Item# 1003304 | Case# 1003303

Product Description	POWER LUBE is a high performance, multi-purpose lubricant that utilizes PTFE and extreme pressure additives to provide unparalleled lubricating performance. It has twice the load carrying capacity of most general purpose lubricants.
Applications	Bearings, gears, linkages, motors, chains, cables, rollers, guide bars, pulleys, cams, valves, ball joints, hinges, slides, cutting tools, taps, dies, pistons, handling equipment, conveyors, hoists, lifts, doors and fans.
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	High Performance Lubricant with PTFE
Net Fill	11 Wt Oz
UPC Code	078254030456
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.1H x 8.3W x 11.1D in
Cases Per Pallet	133
Case Weight	10 lbs
I 2 of 5 Code	30078254030457
Appearance	Light Amber Liquid w/white precipitate
Base Type	Petroleum Solvent
Flash point (F)	<20°F
Flash point (C)	<-7°C
Flammability Class - CPSC	Extremely Flammable
Plastic Safe	No
Film Type	Wet
Film Thickness	Not Determined
Evaporation Rate	Fast

Last revised: 9/11/2020

Page 1 of 2



**Chemical Solutions to Keep You Moving™**

f t i n • 800-272-8963 • [crcindustries.com](http://crcindustries.com)

CRC Industries, Inc. is a global leader in the production of specialty chemicals for maintenance, repair and operational professionals and do-it-yourselfers serving the automotive, industrial, electrical, marine, heavy truck, hardware and aviation markets. CRC trademarked brands include: CRC®, K&W®, Sta-Lube®, SmartWasher®, Marykate®, Weld-Aid®, Ambersil®, KF®, Kontakt Chemie®, Ados®, Action Can®, and Kitten®.

©2019 CRC Industries, Inc.



Dielectric Strength	Not Determined
Working Temp (F)	Max 300°F
Working Temp (C)	Max 148.9°C
Propellant	Carbon Dioxide
NSF Category Code	H2
NSF Number	017403
Aerosol Flammability Level	II
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	23.9
VOC g/L (Consumer Product def)	206.3
VOC lbs/gal (Consumer Prod def)	1.7
VOC Category	Multi-Purpose Lubricant
Restricted from Sale In:	No State Restrictions
Removal (How To)	Remove with petroleum solvents or mineral spirits.