



RTV Silicone Sealant - White, 6.5 Wt Oz No. 14056 | Item# 1004790 | Case# 1004789

Product Description For general-purpose sealing, bonding, protecting and

waterproofing applications. White formulation is designed

for high moisture, indoor/outdoor applications.

Applications Sealing, bonding, protection & waterproofing in HVAC,

electrical, construction, metal working, for filling gaps between mating parts, gearboxes, pumps, motors & for

general gasket sealing.

Unit Package Description 8 Ounce Pressurized Tube with Select-a-BEAD® Nozzle

Brand CRC

Generic Description 1 White Silicone Sealant

Net Fill 6.5 Wt Oz

UPC Code 078254140568

Unit Dimensions 11.5H x 1.75W x 2.5D in

Units Per Case 12

Case Dimensions 11.75H x 7.37W x 7.37D in

Cases Per Pallet 90
Case Weight 7 lbs

I 2 of 5 Code 30078254140569

Appearance White Paste

Flash point (F) $>212^{\circ}F$ Flash point (C) $>100^{\circ}C$

Flammability Class - CPSC None
Spec Gravity Concentrate 1.007

Plastic Safe Yes
Evaporation Rate Slow

Curing Time 24 Hours

Dielectric Strength 25 kV/mm

Working Temp (F) -70 to 400°F

Working Temp (C) -45 to 204.4°C

Viscosity @68 F cP Not Determined

Last revised: 10/8/2019

Page 1 of 2







Gap Fill Not Applicable
Shear StrengthSteel Nuts Not Applicable

Locking Strength Not Applicable
Propellant Nitrogen

Aerosol Flammability Level I

& Bolts

DOT Proper Shipping Name Aerosols, Non-Flammable, Limited Quantity

Military Specification Meets requirements of Mil-A-46106A Number

Federal Specification TT-S-001543A,TT-S-00230-C Number

VOC % (Consumer Product <3.0 def)

VOC g/L (Consumer <31

Product def)

VOC lbs/gal (Consumer <0.26

Prod def)

VOC Category Sealant or Caulking Compound

Removal (How To) Scraping or a gasket remover product

