

# FILTERS, REGULATORS & LUBRICATORS

## 26 Series Filters

The 26 Series Filters offer a balance of compact size and optimum flow. Utilizing a 3/8" die cast aluminum body, this series is perfect for applications where performance, small size and low cost are important. Available in 1/4" and 3/8" port sizes.



### Ordering Information:

Pipe Size	Model
1/4"	26F2
3/8"	26F3

### Options:

Options	Suffix
Automatic Drain	D
Metal Bowl Without Sightglass	M
Metal Bowl With Sightglass	S
5 Micron Element	X

Options are indicated by adding a dash followed by the corresponding suffix(es) in alphabetical order to the model number.

### Specifications

Maximum Supply Pressure:  
 Plastic Bowl: .....150 PSI  
 Metal Bowl: .....250 PSI

Maximum Operating Temp.:  
 Plastic Bowl: .....150° F  
 Metal Bowl: .....250° F

Filter Element:  
 Standard: .....40 Micron  
 Optional: .....5 Micron

Materials:  
 Plastic Bowl: .....Polycarbonate  
 Metal Bowl: .....Zinc Die Cast  
 Body: .....Zinc Die Cast  
 Filter Element: .....Porous Polypropylene

Height: .....6"  
 Maximum Diameter: .....2"  
 Bowl Capacity: .....3.8 oz.

### FEATURES

- ◆ 40 micron or 5 micron filter element.
- ◆ Bowl guard supplied standard.
- ◆ 3.8 oz bowl volume.

**WARNING:** Although polycarbonate bowls are capable of withstanding extreme physical abuse, they are susceptible to damage and may possibly burst when subjected to some cleaning products and synthetic oils, particularly phosphate esters. Should there be any questions regarding their compatibility with your applications, consult the factory or use a metal bowl.

Supply Pressure	Pressure Drop				
	1	2	3	4	5
1/4" at 25 PSI	10	19	22	25	26
3/8" at 25 PSI	15	22	30	36	33
1/4" at 100 PSI	22	32	40	45	50
3/8" at 100 PSI	30	41	52	60	65

**SCFM**

Note: All values are approximate.

## 26 Series Coalescing Filters

The 26 Series Coalescing Filters offer a balance of compact size and optimum flow. Utilizing a 3/8" die cast aluminum body, this series is perfect for applications where performance, small size and low cost are important. Available in 1/4" and 3/8" port sizes.



### Ordering Information:

Pipe Size	Model
1/4"	26C2
3/8"	26C3

### Options:

Options	Suffix
Automatic Drain	D
Metal Bowl Without Sightglass	M
Metal Bowl With Sightglass	S

Options are indicated by adding a dash followed by the corresponding suffix(es) in alphabetical order to the model number.

### Specifications

Maximum Supply Pressure:  
 Plastic Bowl: .....150 PSI  
 Metal Bowl: .....250 PSI

Maximum Operating Temperature:  
 Plastic Bowl: .....150° F  
 Metal Bowl: .....250° F

Materials:  
 Plastic Bowl: .....Polycarbonate  
 Metal Bowl: .....Zinc Die Cast  
 Body: .....Zinc Die Cast  
 Filter Element: .....Porous Polypropylene

Height: .....6"  
 Maximum Diameter: .....2"  
 Bowl Capacity: .....3.8 oz.

### FEATURES

- ◆ Removes 99.97% of solids and fluids down to .3 microns.
- ◆ Bowl guard supplied standard.
- ◆ 3.8 oz bowl volume.
- ◆ Easy "hands only" filter element replacement.

**WARNING:** Although polycarbonate bowls are capable of withstanding extreme physical abuse, they are susceptible to damage and may possibly burst when subjected to some cleaning products and synthetic oils, particularly phosphate esters. Should there be any questions regarding their compatibility with your applications, consult the factory or use a metal bowl.

SCFM at 1.5 PSID Pressure Drop			
Supply Pressure	SCFM	Supply Pressure	SCFM
10 PSI	2.6	60 PSI	7.8
20 PSI	3.6	80 PSI	8.9
30 PSI	4.7	100 PSI	9.9
40 PSI	5.7	120 PSI	11.0
50 PSI	6.8	140 PSI	12.0

Note: All values are approximate.