

## PGX I Goggles Series Specification Sheet

## **PRODUCT DESCRIPTION:**

Consumers committed to sourcing premium products take confidence with PGX1®. Four (4) styles feature design elements that include polycarbonate lens and body with thermal plastic rubber (TPR) seal, multiple points of indirect venting, external liquid diversion channel, and internal perspiration channel. Two adjustable strap options are available including elastic or TPR as well as two lens offerings in clear or gray. Additional feature includes anti-fog lens coating.



## **FEATURES:**

- Polycarbonate body and lens with thermo plastic rubber (TPR) seal
- External liquid diversion channels
- Multiple points of indirect venting for increased airflow
- Available with Elastic or TPR adjustable strap

## **TECHNICAL DATA FOR: PGX120AF**

PGX1 **Series ANSI Z87+** Yes Category Goggles **ANSI D3 SPLASH** Yes Indirect Vented **ANSI D4 DUST** Yes Goggle Type **Dielectric** Yes **ANSI D5 FINE DUST** Yes

Anti-Fog Yes Packaging White Inner Box

Scratch Resistant Yes

Frame Material Polycarbonate

Case Pack 60 pair Case Weight 23.621 oz.

Case Dimensions 19.291 x 18.110 x 18.110 Made In Taiwan

Item No:	Lens Options:	Lens Coating:	Scratch Resistant:	VLT %:	Frame Color:	Goggle
			Resistant.		Color.	Type:
PGX110AF	Clear	Duramass Anti-Fo	og Yes	90	Silver	Indirect Vented
PGX112AF	Gray	Duramass Anti-Fo	og Yes	13	Silver	Indirect Vented
PGX120AF	Clear	Duramass Anti-Fo	og Yes	90	Silver	Indirect Vented
PGX122AF	Gray	Duramass Anti-Fo	og Yes	13	Silver	Indirect Vented

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA

Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrsafety.com



PGX I
Goggles
Series
Specification Sheet