

PGXI Goggles Series Specification Sheet

PRODUCT DESCRIPTION:

Consumers committed to sourcing premium products take confidence with PGX1®. Four (4) styles feature design elements that include polycarbonate lens and body with thermal plastic rubber (TPR) seal, multiple points of indirect venting, external liquid diversion channel, and internal perspiration channel. Two adjustable strap options are available including elastic or TPR as well as two lens offerings in clear or gray. Additional features include anti-fog lens coating.



FEATURES:

- Polycarbonate body and lens with thermo plastic rubber (TPR) seal
- External liquid diversion channels
- Multiple points of indirect venting for increased airflow
- Dual purpose storage/cleaning bag
- Available with Elastic or TPR adjustable strap

TECHNICAL DATA FOR: PGX122AF

Lens	Scratch		Frame	Goaale
Case Dimensions	19.291 x 18.110 x 18.110	Made In	Taiwan	
Case Pack	60 pair Case Weight		23.921 oz.	
Frame Material	Polycarbonate			
Scratch Resistant	Yes			
Anti-Fog	Yes	Packaging	Premium Boxed Per Pair	
Dielectric	Yes	ANSI D5 FINE DUST	Yes	
Goggle Type	Indirect Vented	ANSI D4 DUST	Yes	
Category	Goggles	ANSI D3 SPLASH	Yes	
Series	PGX1 ANSI 287+		Yes	

Item No:	Options:	Lens Coating: Resis	VLT %:	Color:	Type:
PGX110AF	Clear	Duramass Anti-Fog Yes	90	Silver	Indirect Vented
PGX112AF	Gray	Duramass Anti-Fog Yes	13	Silver	Indirect Vented
PGX120AF	Clear	Duramass Anti-Fog Yes	90	Silver	Indirect Vented

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrsafety.com

©2018 MCR Safety - All Rights Reserved



PGXI Goggles Series

Specification Sheet

Item No:	Lens	Lens Coating:	Scratch Resistant:	VLT %:	Frame	Goggle
	Options:				Color:	Туре:
PGX122AF	Gray	Duramass Anti-Fog	g Yes	13	Silver	Indirect Vented

MCR Safety - 1255 Schilling Blvd. W. - Collierville, TN 38017 - USA Phone: 901-795-5810 - Toll Free: 800-955-6887 - Fax: 800-999-3908 - Web: www.mcrsafety.com

©2018 MCR Safety - All Rights Reserved