DELL

SAFETY DATA SHEET

1. Identification

Product identifier BRIGHT EDGE 150

METALWORKING OIL

Other means of identification

SDS number Not applicable

Recommended use METALWORKING OIL

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name DOALL SAWING PRODUCTS

A DOALL COMPANY 2375 Toughy Avenue Elk Grove Village, IL 60007 888-362-5572, Ext 65047

Telephone (General

Information)

Emergency telephone number

Emergency telephone number (outside USA)

1-703-527-3887 (CHEMTREC)

1-800-424-9300 (CHEMTREC)

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement Not available.

Precautionary statement

Prevention Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Wear

protective gloves/protective clothing/eye protection/face protection.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for

advice/attention. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF exposed or concerned: Get medical

advice/attention. Take off contaminated clothing and wash before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store away

from incompatible materials. Store in accordance with local/regional/national/international

regulation.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Material name: BRIGHT EDGE 150

SDS US

Chemical name	Common name and synonyms	CAS number	%
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM		64742-52-5	60 - 100
Other components below reportable I	evels		5 - 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell. Under normal conditions of

intended use, this material is not expected to be an inhalation hazard.

Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing Skin contact

and shoes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing

before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Rinse mouth thoroughly. Do not give liquids. Do not induce vomiting, If vomiting occurs, keep head Ingestion

low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel

unwell.

Most important symptoms/effects, acute and delaved

Exposed individuals may experience eye tearing, redness, and discomfort.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Foam. Dry chemical powder. Carbon dioxide (CO2). Use extinguishing measures that are Suitable extinguishing media

appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Wear suitable protective equipment.

Fire fighting equipment/instructions Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. In the

event of fire and/or explosion do not breathe fumes.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not breathe mist or vapor. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Local authorities should be advised if significant spillages cannot be contained. The product is immiscible with water and will spread on the water surface.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of spillage to drain/aquatic environment. Use appropriate containment to avoid environmental contamination.

Material name: BRIGHT EDGE 150 SDS US 2/7

7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities To maintain product quality, do not store in heat or direct sunlight. Store in original tightly closed container. Room temperature - normal conditions. Do not allow material to freeze. Store away from incompatible materials (see Section 10 of the SDS). Keep this material away from food, drink and animal feed. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	PEL	5 mg/m3	
U.S NIOSH			
	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	STEL	10 mg/m3	
	TWA	5 mg/m3	
ACGIH			
	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	TWA	5 mg/m3	

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Avoid contact with eyes. Eye wash fountain is Eye/face protection

recommended.

Skin protection

Thermal hazards

Hand protection Use protective gloves made of: Nitrile. Other Wear suitable protective clothing and gloves.

< 32 °F (< 0 °C)

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene

Wear appropriate thermal protective clothing, when necessary.

considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

CLEAR Appearance Liquid. **Physical state Form** Liquid. Color Not available.

Chemical Odor Not available. **Odor threshold** Not Applicable

Melting point/freezing point

Initial boiling point and boiling

range

Not Applicable

300 °F (148.9 °C) Cleveland Closed Cup Flash point

Evaporation rate Not available. Not applicable. Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Not available. Vapor pressure Vapor density Not available. Relative density Not available.

Partition coefficient

(n-octanol/water)

Solubility(ies)

Not available.

Insoluble in Water

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Not available. **Viscosity**

Other information

Specific gravity 0.91 **VOC ASTM D2369** 12 %

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use. Hazardous polymerization does not

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials.

Avoid contact with oxidizers or reducing agents. Incompatible materials

Hazardous decomposition

products

Smoke, fumes, hydrogen chloride, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Prolonged inhalation may be harmful. May cause irritation to the respiratory system. Inhalation

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. Skin contact

Direct contact with eyes may cause temporary irritation. Eye contact

May be harmful if swallowed and enters airways. Droplets of the product aspirated into the lungs Ingestion

through ingestion or vomiting may cause a serious chemical pneumonia. Expected to be a low

ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation. Exposed individuals may experience eye

tearing, redness, and discomfort.

Information on toxicological effects

May be harmful if swallowed and enters airways. Expected to be a low hazard for usual industrial **Acute toxicity**

or commercial handling by trained personnel.

Material name: BRIGHT EDGE 150 SDS US 4/7 Components Species Test Results

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM (CAS 64742-52-5)

Acute

Dermal

LD50 Rabbit > 5000 mg/kg

Inhalation

LC50 Rat 5.7 mg/l, 4 hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation. Defatting, drying and cracking of skin.

Serious eye damage/eye

irritation

May be irritating to eyes. Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure Aspiration hazard Not classified.

May be harmful if swallowed and enters airways. If aspirated into lungs during swallowing or

vomiting, may cause chemical pneumonia, pulmonary injury or death.

Chronic effects Not expected to be hazardous by OSHA criteria.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM (CAS 64742-52-5)

Aquatic Acute

Fish LC50 Fish > 100 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsConsult authorities before disposal. Do not contaminate ponds, waterways or ditches with

chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

^{*} Estimates for product may be based on additional component data not shown.

^{*} Estimates for product may be based on additional component data not shown.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Not listed.

US. Pennsylvania Worker and Community Right-to-Know Law

OILS, LARD (CAS 8016-28-2)

US. Rhode Island RTK

Not regulated.

California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions) This product is subject to SCAQMD Rule 1144; it is not compliant and shall not be sold and used in the SCAQMD. The VOC content of the product is 92 g/L, measured by ASTM Method 1868-10.

On inventory or exempt (yes/no)*

This product has a specified VOC limit of 75 g/L.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories Country(s) or region

Country(s) or region	inventory name	On inventory or exempt (yes/no)
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Inventory name

 Issue date
 03-23-2015

 Revision date
 04-28-2015

Version # 02

Further information Not available.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision Information Physical & Chemical Properties: Multiple Properties

Material name: BRIGHT EDGE 150 SDS US