



SAFETY DATA SHEET

1. Identification

Product identifier	POWER CUT ULTRA METALWORKING FLUID
Other means of identification	
SDS number	Not applicable
Recommended use	METALWORKING FLUID
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Company name	DOALL SAWING PRODUCTS A DOALL COMPANY 2375 Touhy Avenue Elk Grove Village, IL 60007 888-362-5572, Ext 65047
Telephone (General Information)	
Emergency telephone number	1-800-424-9300 (CHEMTREC)
Emergency telephone number (outside USA)	1-703-527-3887 (CHEMTREC)

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Serious eye damage/eye irritation Reproductive toxicity	Category 2 Effects on or via lactation
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Warning
Hazard statement	Causes serious eye irritation. May cause harm to breast-fed children.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not breathe mist or vapor. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.
Response	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention.
Storage	Store in accordance with local/regional/national/international regulation. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store away from incompatible materials.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM		64742-52-5	60 - 100
C14-C17 MEDIUM CHAIN CHLORINATED PARAFFIN		63449-39-8	5 - 10
DIETHYLENE GLYCOL		111-46-6	0.5 - 5.0
PETROLEUM SULFONIC ACID, SODIUM SALT		68608-26-4	0.5 - 5.0
2-BUTOXYETHANOL		111-76-2	0.1 - 1
Other components below reportable levels			7 - 13

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

Skin contact

Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth thoroughly. Do not give liquids. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention.

5. Fire-fighting measures

Suitable extinguishing media

Foam. Dry chemical powder. Carbon dioxide (CO₂). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Wear suitable protective equipment.

Fire fighting equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained. This product is miscible in water. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of spillage to drain/aquatic environment. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not breathe mist or vapor. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. To maintain product quality, do not store in heat or direct sunlight. Store in original tightly closed container. Room temperature - normal conditions. Store away from incompatible materials (see Section 10 of the SDS). Keep this material away from food, drink and animal feed. Do not allow material to freeze. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

	Type	Value
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	PEL	5 mg/m3

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

	Type	Value
2-BUTOXYETHANOL (CAS 111-76-2)	PEL	240 mg/m3 50 ppm

U.S. - NIOSH

	Type	Value
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	STEL	10 mg/m3
	TWA	5 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

	Type	Value
2-BUTOXYETHANOL (CAS 111-76-2)	TWA	24 mg/m3 5 ppm

ACGIH

	Type	Value
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	TWA	5 mg/m3

US. ACGIH Threshold Limit Values

	Type	Value
2-BUTOXYETHANOL (CAS 111-76-2)	TWA	20 ppm

Exposure guidelines**US - California OELs: Skin designation**

2-BUTOXYETHANOL (CAS 111-76-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-BUTOXYETHANOL (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

2-BUTOXYETHANOL (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-BUTOXYETHANOL (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-BUTOXYETHANOL (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye wash fountain is recommended.

Skin protection

Hand protection Use protective gloves made of: Nitrile.

Other Wear suitable protective clothing and gloves. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	CLEAR
Physical state	Liquid.
Form	Liquid.
Color	Not available.
Odor	CHEMICAL
Odor threshold	Not available.
pH	Not Applicable
Melting point/freezing point	< 32 °F (< 0 °C)
Initial boiling point and boiling range	> 212 °F (> 100 °C)
Flash point	> 311 °F (> 155 °C) Cleveland Open Cup
Evaporation rate	Like water when diluted
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.

Relative density	Not available.
Solubility(ies)	100 % Water Miscible
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
pH in aqueous solution	9.3 @ 5%
Specific gravity	0.94
VOC ASTM D2369	16 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Avoid contact with oxidizers or reducing agents.
Hazardous decomposition products	Smoke, fumes, hydrogen chloride, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May be irritating to the skin. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May be harmful if swallowed and enters airways. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.
---	--

Information on toxicological effects

Acute toxicity	Expected to be a low hazard for usual industrial or commercial handling by trained personnel.
-----------------------	---

Components	Species	Test Results
2-BUTOXYETHANOL (CAS 111-76-2)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	400 mg/kg
<i>Inhalation</i>		
LC50	Mouse	700 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
<i>Oral</i>		
LD50	Guinea pig	1.2 g/kg
	Mouse	1.2 g/kg
	Rabbit	0.32 g/kg
	Rat	560 mg/kg
DIETHYLENE GLYCOL (CAS 111-46-6)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	11890 mg/kg

Components	Species	Test Results
<i>Oral</i> LD50	Cat	3300 mg/kg
	Dog	9000 mg/kg
	Guinea pig	8700 mg/kg
	Mouse	13.3 g/kg
	Rabbit	26.9 g/kg
	Rat	12565 mg/kg

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM (CAS 64742-52-5)

Acute

Dermal

LD50 Rabbit > 5000 mg/kg

Inhalation

LC50 Rat 5.7 mg/l, 4 hours

Oral

LD50 Rat > 5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Defatting, drying and cracking of skin.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-BUTOXYETHANOL (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Contains a substance which causes risk of hazardous effects to the environment. Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
2-BUTOXYETHANOL (CAS 111-76-2)		
Aquatic		
Fish	LC50 Inland silverside (<i>Menidia beryllina</i>)	1250 mg/l, 96 hours
C14-C17 MEDIUM CHAIN CHLORINATED PARAFFIN (CAS 63449-39-8)		
Aquatic		
Fish	LC50 Bluegill (<i>Lepomis macrochirus</i>)	> 0.1 mg/l, 96 hours
DIETHYLENE GLYCOL (CAS 111-46-6)		
Aquatic		
Fish	LC50 Western mosquitofish (<i>Gambusia affinis</i>)	> 32000 mg/l, 96 hours

Components	Species	Test Results
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM (CAS 64742-52-5)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Fish > 100 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)
2-BUTOXYETHANOL 0.83

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

- Disposal instructions** Consult authorities before disposal. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
- Local disposal regulations** Dispose in accordance with all applicable regulations.
- Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
- Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
- Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

- DOT**
- UN number** UN3082
 - UN proper shipping name** Environmentally hazardous substances, liquid, n.o.s. (C14-C17 MEDIUM CHAIN CHLORINATED PARAFFIN), MARINE POLLUTANT
 - Transport hazard class(es)**
 - Class** 9
 - Subsidiary risk** -
 - Label(s)** 9
 - Packing group** III
 - Environmental hazards**
 - Marine pollutant** Yes
 - Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.
 - Special provisions** 8, 146, 335, IB3, T4, TP1, TP29
 - Packaging exceptions** 155
 - Packaging non bulk** 203
 - Packaging bulk** 241

Supplemental Information: 49CFR 171.4 excludes "non-bulk"packages (119 gallons or less) from Marine Pollutant Requirements unless all or part of the shipment is by vessel.

- IATA**
- UN number** UN3082
 - UN proper shipping name** Environmentally hazardous substance, liquid, n.o.s. (C14-C17 MEDIUM CHAIN CHLORINATED PARAFFIN)
 - Transport hazard class(es)**
 - Class** 9
 - Subsidiary risk** -
 - Packing group** III
 - Environmental hazards** Yes
 - ERG Code** 9L
 - Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed.
Cargo aircraft only Allowed.

IMDG

UN number UN3082
UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C14-C17 MEDIUM CHAIN CHLORINATED PARAFFIN), MARINE POLLUTANT

Transport hazard class(es)

Class 9
Subsidiary risk -

Packing group III

Environmental hazards

Marine pollutant Yes

EmS F-A, S-F

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

DOT; IATA; IMDG



Marine pollutant



General information DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311 and 312 if specific threshold criteria are met or exceeded.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

2-BUTOXYETHANOL (CAS 111-76-2)

US. New Jersey Worker and Community Right-to-Know Act

2-BUTOXYETHANOL (CAS 111-76-2)

US. Pennsylvania Worker and Community Right-to-Know Law

2-BUTOXYETHANOL (CAS 111-76-2)
DIETHYLENE GLYCOL (CAS 111-46-6)

US. Rhode Island RTK

Not regulated.

California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions)

This product is subject to SCAQMD Rule 1144; it is compliant and may be sold and used in the SCAQMD. The VOC content of the product is 105 g/L, measured by ASTM Method E-1868-10. This product has a specified use dilution VOC limit of 75 g/L, the maximum dilution concentration is 71 % to maintain compliance.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 3-01-2015

Revision date

Version # 02

Further information Not available.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision Information Physical & Chemical Properties: Multiple Properties