DOLL

SAFETY DATA SHEET

1. Identification

Product identifier POWER CUT 470

METALWORKING FLUID

Other means of identification

SDS number Not applicable

Recommended use METALWORKING FLUID

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name DOALL SAWING PRODUCTS

A DOALL COMPANY 2375 Toughy Avenue Elk Grove Village, IL 60007 888-362-5572, Ext 65047

Telephone (General

Information)

Emergency telephone

number

Emergency telephone number (outside USA)

1-703-527-3887 (CHEMTREC)

1-800-424-9300 (CHEMTREC)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Serious eye damage/eye irritation Category 2

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes serious eye irritation.

Precautionary statement

Prevention Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Wear

protective gloves/protective clothing/eye protection/face protection.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical

advice/attention. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician. Take off contaminated clothing and wash

before reuse. Collect spillage.

Storage Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store away

from incompatible materials. Store in accordance with local/regional/national/international

regulation.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

 Material name: POWER CUT 470
 SDS US

 Version #: 02
 Issue date: 03-24-2015

 1 / 8

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM		64742-52-5	60 - 100
PETROLEUM SULFONIC ACID, SODIUM SALT		68608-26-4	7 - 13
DIETHYLENE GLYCOL		111-46-6	1 - 5
TALL OIL		8002-26-4	1 - 5
Other components below reportable le	vels		1 - 5

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell. Under normal conditions of

intended use, this material is not expected to be an inhalation hazard.

Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing Skin contact

and shoes. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing

before reuse.

Immediately flush eves with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion Rinse mouth thoroughly. Do not give liquids. Never give anything by mouth to a victim who is

unconscious or is having convulsions. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in General information

attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Foam. Dry chemicals. Carbon dioxide (CO2). Use extinguishing measures that are appropriate to

Do not use water jet as an extinguisher, as this will spread the fire.

local circumstances and the surrounding environment.

During fire, gases hazardous to health may be formed.

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters Wear suitable protective equipment.

Fire fighting equipment/instructions

Specific methods

General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials. Move

containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: POWER CUT 470 SDS US

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained.

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of

spillage to drain/aquatic environment. Use appropriate containment to avoid environmental

contamination.

7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with eyes. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

To maintain product quality, do not store in heat or direct sunlight. Store in original tightly closed container. Room temperature - normal conditions. Store away from incompatible materials (see Section 10 of the SDS). Keep this material away from food, drink and animal feed. Do not allow material to freeze. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	PEL	5 mg/m3	
U.S NIOSH			
	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	STEL	10 mg/m3	
	TWA	5 mg/m3	
ACGIH			
	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM (CAS 64742-52-5)	TWA	5 mg/m3	

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is

recommended.

Skin protection

Hand protection Use protective gloves made of: Nitrile.

Other Wear suitable protective clothing and gloves.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Material name: POWER CUT 470

Version #: 02 Issue date: 03-24-2015 3 / 8

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance CLEAR
Physical state Liquid.
Form Liquid

Form Liquid.
Color Not available.

Odor CHEMICAL
Odor threshold Not available.

PH Not Applicable
Melting point/freezing point < 32 °F (< 0 °C)
Initial boiling point and boiling > 212 °F (> 100 °C)

range

Flash point 325 °F (162.8 °C) Cleveland Open Cup

Evaporation rate Like water when diluted

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit - upper Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies) 100 % Water Miscible

Partition coefficient (n-octanol/water)

Not available.

Not available.

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

pH in aqueous solution 9.1 @ 5% Specific gravity 0.94 VOC ASTM D2369 11 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use. Hazardous polymerization does not

occur.

Conditions to avoid Heat, flames and sparks. Temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials Avoid contact with oxidizers or reducing agents.

Hazardous decomposition

products

Smoke, fumes, and oxides of carbon

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful. May be harmful if swallowed and enters airways.

Material name: POWER CUT 470

SDS US

4 / 9

Skin contact May be irritating to the skin. Frequent or prolonged contact may defat and dry the skin, leading to

discomfort and dermatitis.

Eye contact Causes serious eye irritation. Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision

Information on toxicological effects

Acute toxicity Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Compor	nents	Species	Test Results		
DIETHYLENE GLYCOL (CAS 111-46-6)					
	Acute				
	Dermal				
	LD50	Rabbit	11890 mg/kg		
	Oral				
	LD50	Cat	3300 mg/kg		
		Dog	9000 mg/kg		
		Guinea pig	8700 mg/kg		
		Mouse	13.3 g/kg		
		Rabbit	26.9 g/kg		
		Rat	12565 mg/kg		
SEVERE	ELY-HYDROTREATED NAPI	HTHENIC PETROLEUM (CAS 64742-52-5)			
	Acute				
	Dermal				
	LD50	Rabbit	> 5000 mg/kg		
	Inhalation				
	LC50	Rat	5.7 mg/l, 4 hours		
	Oral				
	LD50	Rat	> 5000 mg/kg		
TALL OIL (CAS 8002-26-4)					
	Acute				
	Dermal LD50	Rat	> 2000 mg/kg		
	Oral	Rat	> 2000 Hig/kg		
	LC50	Rat	> 2000 mg/kg		
	LD50	Rat	66 g/kg		
	Chronic	Nat	oo g/kg		
	Dermal				
	NOAEL	Rat	> 50 mg/kg		
	Oral				
	NOAEL	Rat	> 200 mg/kg		
			3 3		

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Defatting, drying and cracking of skin.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

Aspiration hazard

Not classified.

repeated exposure

If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary

injury or death.

Prolonged inhalation may be harmful. **Chronic effects**

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Species Test Results**

DIETHYLENE GLYCOL (CAS 111-46-6)

Aquatic

LC50 Fish Western mosquitofish (Gambusia affinis) > 32000 mg/l, 96 hours

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM (CAS 64742-52-5)

Aquatic Acute

LC50 Fish Fish > 100 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

3.2 - 6.8TALL OIL

Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Consult authorities before disposal. Do not contaminate ponds, waterways or ditches with

chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

Material name: POWER CUT 470 SDS US

6/8

^{*} Estimates for product may be based on additional component data not shown.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311 and 312 if specific threshold criteria are met or exceeded.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

> Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Not listed.

US. Pennsylvania Worker and Community Right-to-Know Law

DIETHYLENE GLYCOL (CAS 111-46-6)

US. Rhode Island RTK

Not regulated.

California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions)

This product is subject to SCAQMD Rule 1144; it is compliant and may be sold and used in the SCAQMD. The VOC content of the product is 95 g/L, measured by ASTM Method E-1868-10. This product has a specified use dilution VOC limit of 75 g/L, the maximum dilution concentration is 79

% to maintain compliance.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No

Material name: POWER CUT 470 SDS US

Country(s) or region Inventory name On inventory or exempt (yes/no)* Inventory of Existing Chemical Substances in China (IECSC) China European Inventory of Existing Commercial Chemical Europe Yes Substances (EINECS) European List of Notified Chemical Substances (ELINCS) Europe No Inventory of Existing and New Chemical Substances (ENCS) Japan Yes Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes Philippines Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

 Issue date
 03-24-2015

 Revision date
 04-28-2015

Version # 02

Further information Not available.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision Information Physical & Chemical Properties: Multiple Properties

Material name: POWER CUT 470 SDS US

Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)