

S812HA

Slot Drill



| d ₁ R mm | Ch ±0.03x45° mm | d ₂ R _{h6} mm | l ₂ mm | l ₁ mm | z | e-code | USD |
|---------------------------|-----------------------|---|----------------------|----------------------|---|------------|-----------|
| 2.00 | - | 6 | 6 | 57 | 2 | S812HA2.0 | 53.60 |
| 2.50 | 0.08 | 6 | 7 | 57 | 2 | S812HA2.5 | 56.60 |
| 3.00 | 0.08 | 6 | 7 | 57 | 2 | S812HA3.0 | 53.60 |
| 3.50 | 0.08 | 6 | 7 | 57 | 2 | S812HA3.5 | 59.50 |
| 4.00 | 0.13 | 6 | 8 | 57 | 2 | S812HA4.0 | 58.30 |
| 4.50 | 0.13 | 6 | 8 | 57 | 2 | S812HA4.5 | 65.40 |
| 5.00 | 0.13 | 6 | 10 | 57 | 2 | S812HA5.0 | 59.50 |
| 6.00 | 0.13 | 6 | 10 | 57 | 2 | S812HA6.0 | 59.50 |
| 7.00 | 0.13 | 8 | 13 | 63 | 2 | S812HA7.0 | 89.30 |
| 8.00 | 0.20 | 8 | 16 | 63 | 2 | S812HA8.0 | 1) 83.30 |
| 9.00 | 0.20 | 10 | 16 | 72 | 2 | S812HA9.0 | 1) 119.00 |
| 10.00 | 0.20 | 10 | 19 | 72 | 2 | S812HA10.0 | 1) 110.00 |
| 12.00 | 0.20 | 12 | 22 | 83 | 2 | S812HA12.0 | 1) 151.00 |
| 14.00 | 0.20 | 14 | 22 | 83 | 2 | S812HA14.0 | 1) 191.00 |
| 16.00 | 0.20 | 16 | 26 | 92 | 2 | S812HA16.0 | 1) 249.00 |
| 18.00 | 0.20 | 18 | 26 | 92 | 2 | S812HA18.0 | 1) 322.00 |
| 20.00 | 0.30 | 20 | 32 | 104 | 2 | S812HA20.0 | 1) 387.00 |

1) ± 0.05x45° mm