



Technical Data Sheet

Remover & Prep For Layout Fluids & Staining Colors

FEATURES

- Preferred solution for all surface preparations, removal and dilution of Dykem Staining Colors and Layout Fluids.
- Tests have proven that Layout Fluids and Staining Colors adhere better to surfaces that are prepared with this product.
- Ideal for reducing thickness/drying time of Layout Fluids and Staining Colors.
- Low in VOC's (volatile organic compounds).
- Works great for flushing out lines and nozzles.
- Available in multiple package sizes.
- Do not contain any reportable amounts of Xylene.

MATERIALS COMPATIBILITY

- Safe on most surfaces.
- Surface tests should be run to determine compatibility prior to use.

HEALTH AND SAFETY

- Flammable liquid and vapor. Keep away from heat, sparks and flame. Use only with adequate ventilation. Avoid contact with skin and eyes.
- Refer to SDS (Safety Data Sheet) for complete information on health and safety. Visit our website to obtain SDS.

DIRECTIONS FOR USE

- Apply to surface and allow staining color or layout fluid to liquefy.
- Wipe off with a cloth or paper towel.

AVAILABLE IN:

Part #:

16 oz. Aerosol	82038
1 Quart	82638
1 Gallon	82738
5 Gallon Pail	82838
55 Gallon Drum	82938

PHYSICAL PROPERTIES

Appearance:	Clear
Odor:	Sweet
Specific gravity:	<1
VOC level:	36% - 49% by weight
Flash point:	-4°F
Dry Time*:	< 30 seconds

* Note: Exact drying time may vary depending on film thickness.