

**Model: FP09R**



## Description:

Reusable Roof Anchor. Designed for attachment to a suitable structure on residential roofing.

Maximum free fall distance should be limited to 6 feet (1.8 meter). All 10 screws need to be used.

Choose CSA certified full body harness, energy absorber, lifeline and components when using Roof Anchor.

<b>SIZE</b>	<i>Unique</i>	<b>MADE IN</b>	<i>Canada</i>
<b>TYPE</b>	<i>Reusable Roof Bracket</i>	<b>MATERIALS</b>	<i>High Strength Steel</i>
<b>CSA CLASS</b>	<i>NA</i>	<b>MAX WORK LOAD</b>	<i>Single Person Usage Only (400 lbs)</i>
<b>DIMENSION</b>	<i>14.28 in x 3.01 in (362 mm x 76 mm)</i>	<b>WEB MIN TENSILE</b>	<i>6000 lbs (27 kN)</i>
<b>COLOR</b>	<i>Red Painted</i>	<b>BRACKET TENSILE STRENGTH</b>	<i>5000 lbs (22.2 kN)</i>
<b>SCREWS</b>	<i>8 x2-1/2" (10 pieces)</i>	<b>WEIGHT</b>	<i>39.5 oz (1120 g)</i>

**Training and Proper Use:** Please refer to product manual included with the products prior to use.  
**For Additional Information:** 1-877-446-3278

Revision 1, October 20, 2015

### Head Office

2477, Michelin, Laval, Qc H7L 5B9  
 T: (450) 622-7374/ 1 877 446-3278  
 F: (450) 622-2243/ 1 877 463-2789

### Fall Protection Manufacturing

175B Admiral Blvd., Mississauga, ON L5T 2T3  
 T: (905) 565-9990  
 F: (905) 565-9906