

Models : FP1-102W, FP1-102WA, FP1-102WB, FP1-102WC (single leg)

FP1-102DW, FP1-102DWA, FP1-102DWB, FP1-102DWC (dual leg)

DESCRIPTION



7 feet (2.15 m) single leg or dual leg Web Self-Retracting Lifeline (WSRL).

The Type 1 WSRL performs only a locking (fall-stopping) function.

These units are for use as part of a complete fall arrest system that must also include a CSA and/or ANSI approved full body harness and a suitable anchorage and/or anchorage connector.

Each SRL must be anchored to a suitable structure capable of resisting a static load of 3600 lbs. (16 kN) if certified, or 5000 lbs (22.2 kN) if not certified.

This unit is for a single user only.

SIZE	7 ft (2.15 m)	MADE IN	Taiwan
TYPE	Webbing Self-Retracting Lifeline	MATERIALS	1 inch (25 mm) webbing; High Strength Steel Carabiner and Snap
CSA CLASS	Type 1	MAX WORK LOAD	310 lbs (140 kg)
STANDARDS	CSA Z259.2.2-98, ANSI Z359.1-2007	MAX ARREST FORCE	8 kN (1800 lbs) when tested in accordance with ANSI Z359.1-2007
HARDWARE	Certified to CSA Z259.12	MAX ARREST DISTANCE	39.37 in (1 m)
COLOR	Black Cover	HARDWARE MIN TENSILE	5000 lbs (22.2 kN)
WEIGHT	2.85 lbs. – 3.75 lbs. (1.3 kg – 1.7 kg)		

Training and Proper Use: Please refer to product manual included with the products prior to use.

For Additional Information: 1-877-446-3278

Head Office

2477, Michelin, Laval, Qc H7L 5B9
T: (450) 622-7374/ 1 877 446-3278
F: (450) 622-2243/ 1 877 463-2789

Fall Protection Manufacturing

175B Admiral Blvd., Mississauga, ON L5T 2T3
T: (905) 565-9990
F: (905) 565-9906