

Model: FP131/XX (XX=length in inches)

Description:

Automatic rope grab with DYNA-ONE energy absorber lanyard. Rope grab with large eye and snap hook with 3/4" gate opening. Certified for use with 5/8" (16mm) Dynamic vertical lifeline.



SIZE	30 inches long	MADE IN	Canada
TYPE	Automatic Rope Grab	MATERIALS	1 3/4 in Polyester Webbing for Soft Pack and Cold Formed Steel for Rope Grab
CSA CLASS	Automatic	MAX WORK LOAD	100-352 lbs (45-160kg)
STANDARDS	Certified to CSA Z259.2.5-17. Meets and exceeds CSA Z259.11-17, ANSI Z359.1-07	WEB MIN TENSILE	6000 lbs (27 kN)
HARDWARE	Certified to CSA Z259.12-16; ANSI/ASS Z359.1-2007	ROPE GRAB MIN TENSILE	5000 lbs (22.2 kN)
COLOR	Black, Silver	HARDWARE MIN TENSILE	5000 lbs (22.2 kN)
		WEIGHT	2.6 lbs (1.18 kg)

Training and Proper Use: Please refer to product manual included with the products prior to use.
For Additional Information: 1-877-446-3278

Head Office

2477, Michelin, Laval, Qc H7L 5B9
 T: (450) 622-7374/ 1 877 446-3278
 F: (450) 622-2243/ 1 877 463-2789

Fall Protection Manufacturing

175 Admiral Blvd., Mississauga, On L5T 2T3
 T: (905) 565-9990
 F: (905) 565-9906

Revision 1, January 20, 2021