

## Model: FP63211x, FP63213x,

## FP63214x



## **Description:**

Web adjustable Lanyard. The webbing is made of polyester material and can adjust from 60% to 100% of the length.

This product shall be integrally connected to other fall arrest system components or elements.

This product is certified by CSA; Meet and exceed the *ANSI* & *OSHA* as well.

Single user only.

SIZE	Adjustable	WEIGTH	1.24 lbs (0.56 kg)
ТҮРЕ	Web Lanyard	MATERIALS	High Strength Steel Snaps; 1" Width Polyester Webbing
CSA CLASS	Class B	MAX WORK LOAD	400 lbs (180 kg)
STANDARDS	CSA Z259.11-17, ANSI Z359.1-07	HARDWARE MIN TENSILE	6000 lbs (27 kN)
HARDWARE	Certified to CSA Z259.12-16; ANSI/ASS Z359.12-19	MAX. ARREST FORCE	1300 lbs (6 kN) or less
COLOR	Golden or Silver Snaps; Red Lanyard	MADE IN	Canada

Training and Proper Use: Please refer to product manual included with the products prior to use. For Additional Information: 1-877-446-3278

**Revision 1, December 16, 2020** L'information en français est disponible

Head Office 2477, Michelin, Laval, Qc H7L 5B9 T: (450) 622-7374/ 1 877 446-3278 F: (450) 622-2243/ 1 877 463-2789 **Fall Protection Manufacturing** 175 Admiral Blvd., Mississauga, On L5T 2T3 T: (905) 565-9990 F: (905) 565-9906

