

Model : FPE2001D,3D,3SD,5D,6D



Description:

The Dyna-1FR Welders harness is made of Kevlar webbing and offers maximum protection against cuts, abrasion and high heat caused by sparks and flames. The metal components are all coated which makes the harness completely dielectric

Using *Dynamic* certified Kevlar lanyards with this harness is highly recommended.

SIZE	XS, S, M, L, REG(Regular), XL, 2XL, 3XL	HARDWARE MATERIAL	High Strength Steel
TYPE	Full Body Harness	WEBBING MATERIALS	1 ¾ in Wide KEVLAR Webbing
CSA CLASSIFICATION	Class A (Fall Arrest) or AP (Fall and positioning) or AE (fall and confine space) APE (Fall ,positioning and confine space) APEL (Fall , positioning ,confine space, ladder)	MAX WORK LOAD	400 lbs (180 kg)
STANDARDS	CSA Z259.10, ANSI Z359.1, OSHA 1926.502, ASTM F887-13	WEB MIN TENSILE	9000 lbs (40 kN)
HARDWARE STANDARD	Certified to CSA Z259.10-12	D-RING MIN TENSILE	5000 lbs (22 kN)
COLOR	Black for Webbing and for Hardware Coated	HARDWARE MIN TENSILE	5000 lbs (22 kN)
WEIGHT	2.8 lbs. (1.27 kg)	MADE IN	Canada

**Training and Proper Use: Please refer to product manual included with the products prior to use.
For Additional Information: 1-877-446-3278**

Revision :July 4 , 2017

L'information en français est disponible

Head Office

2477, Michelin, Laval, Qc H7L 5B9
T: (450) 622-7374/ 1 877 446-3278
F: (450) 622-2243/ 1 877 463-2789

Fall Protection Manufacturing

175B Admiral Blvd., Mississauga, ON L5T 2T3
T: (905) 565-9990
F: (905) 565-9906