



# EXOCARB<sup>®</sup> MAX

Maximum Performance End Mills for Hardened Steels

## List 9191

CBN-SXB, 2 Flute, Ball End, CBN

<b>SPEED FEED</b> P1202	<b>CBN</b>	<b>BR</b>	<b>30°</b>	<b>SHANK</b> h6
<b>Radius Tolerance</b>				
0.4 ≤ D ≤ 3		±0.005mm		



Units: mm

EDP Number	Mill Diameter	Overall Length	Length of Cut	Neck Length	Shank Diameter
	D	L	Lc	L1	d
8525304	0.4	45	0.3	1.2	4
8525305	0.5	45	0.3	1.5	4
8525306	0.6	45	0.4	1.8	4
8525307	0.7	45	0.5	2.1	4
8525308	0.8	45	0.5	2.4	4
8525309	0.9	45	0.6	2.7	4
8525310	1.0	45	0.6	2.5	4
8525210	1.0	50	0.6	2.5	6
8525211	1.1	50	0.7	2.8	6
8525212	1.2	50	0.7	3.0	6
8525213	1.3	50	0.8	3.3	6
8525214	1.4	50	0.8	3.5	6
8525215	1.5	50	0.9	3.8	6
8525216	1.6	50	1.0	4.0	6

EDP Number	Mill Diameter	Overall Length	Length of Cut	Neck Length	Shank Diameter
	D	L	Lc	L1	d
8525217	1.7	50	1.0	4.3	6
8525218	1.8	50	1.1	4.5	6
8525219	1.9	50	1.1	4.8	6
8525220	2.0	50	1.2	5.0	6
8525221	2.1	50	1.3	4.2	6
8525222	2.2	50	1.3	4.4	6
8525223	2.3	50	1.4	4.6	6
8525224	2.4	50	1.4	4.8	6
8525225	2.5	50	1.5	5.0	6
8525226	2.6	50	1.6	5.2	6
8525227	2.7	50	1.6	5.4	6
8525228	2.8	50	1.7	5.6	6
8525229	2.9	50	1.7	5.8	6
8525230	3.0	50	1.8	6.0	6

Packed: 1 pc.  
Available Bright only.



## List 9192

CBN-LN-SXB, 2 Flute, Long Neck, Ball End, CBN

<b>SPEED FEED</b> P1203	<b>CBN</b>	<b>BR</b>	<b>30°</b>	<b>SHANK</b> h6
<b>Radius Tolerance</b>				
0.4 ≤ D ≤ 3		±0.050mm		



Units: mm

EDP Number	Mill Diameter	Overall Length	Length of Cut	Neck Length	Shank Diameter
	D	L	Lc	L1	d
8525622	0.4	45	0.3	2.0	4
8525623	0.4	45	0.3	3.0	4
8525624	0.6	45	0.4	2.0	4

EDP Number	Mill Diameter	Overall Length	Length of Cut	Neck Length	Shank Diameter
	D	L	Lc	L1	d
8525855	1.0	50	0.6	5.0	6
8525856	1.0	50	0.6	6.0	6