



EXOCARB® WXL®

Premium Performance Carbide End Mills with OSG's Proprietary WXL® Coating

List 3790

WXL-LN-EBD, 2 Flute, Regular Length, Long Neck, Ball End, Rib Processing

SPEED FEED P1139-1148	CARBIDE	WXL	REG	30°	SHANK h6
--------------------------	---------	-----	-----	-----	-------------

±5µm Radius Tolerance



Units: mm

EDP Number	Mill Diameter	Overall Length	Length of Cut	Neck Length	Neck Dia.	Shank Diameter	EDP Number	Mill Diameter	Overall Length	Length of Cut	Neck Length	Neck Dia.	Shank Diameter
	D	L	Lc	L1	d2	d		D	L	Lc	L1	d2	d
3110103	0.1	45	0.1	0.3	0.085	4	3110560	0.5	45	0.4	6.0	0.45	4
3110105	0.1	45	0.1	0.5	0.085	4	3110570	0.5	45	0.4	7.0	0.45	4
3110203	0.2	45	0.2	0.3	0.18	4	3110580	0.5	45	0.4	8.0	0.45	4
3110205	0.2	45	0.2	0.5	0.18	4	3110590	0.5	45	0.4	9.0	0.45	4
3110207	0.2	45	0.16	0.75	0.18	4	3110600	0.5	45	0.4	10	0.45	4
3110210	0.2	45	0.2	1.0	0.18	4	3110610	0.6	45	0.5	1.0	0.55	4
3110212	0.2	45	0.16	1.25	0.18	4	3110615	0.6	45	0.5	1.5	0.55	4
3110215	0.2	45	0.2	1.5	0.18	4	3110620	0.6	45	0.5	2.0	0.55	4
3110217	0.2	45	0.16	1.75	0.18	4	3110625	0.6	45	0.5	2.5	0.55	4
3110220	0.2	45	0.16	2.0	0.18	4	3110630	0.6	45	0.5	3.0	0.55	4
3110225	0.2	45	0.16	2.5	0.18	4	3110635	0.6	45	0.5	3.5	0.55	4
3110230	0.2	45	0.16	3.0	0.18	4	3110640	0.6	45	0.5	4.0	0.55	4
3110305	0.3	45	0.24	0.5	0.28	4	3110645	0.6	45	0.5	4.5	0.55	4
3110306	0.3	45	0.24	0.6	0.28	4	3110650	0.6	45	0.5	5.0	0.55	4
3110307	0.3	45	0.24	0.75	0.28	4	3110655	0.6	45	0.5	5.5	0.55	4
3110310	0.3	45	0.2	1.0	0.28	4	3110660	0.6	45	0.5	6.0	0.55	4
3110312	0.3	45	0.24	1.25	0.28	4	3110665	0.6	45	0.5	6.5	0.55	4
3110315	0.3	45	0.2	1.5	0.28	4	3110670	0.6	45	0.5	7.0	0.55	4
3110317	0.3	45	0.24	1.75	0.28	4	3110675	0.6	45	0.5	7.5	0.55	4
3110320	0.3	45	0.2	2.0	0.28	4	3110680	0.6	45	0.5	8.0	0.55	4
3110322	0.3	45	0.24	2.25	0.28	4	3110685	0.6	45	0.5	8.5	0.55	4
3110325	0.3	45	0.24	2.5	0.28	4	3110690	0.6	45	0.5	9.0	0.55	4
3110327	0.3	45	0.24	2.75	0.28	4	3110695	0.6	45	0.5	9.5	0.55	4
3110330	0.3	45	0.24	3.0	0.28	4	3110700	0.6	45	0.5	10	0.55	4
3110335	0.3	45	0.24	3.5	0.28	4	3110711	0.6	45	0.5	11	0.55	4
3110340	0.3	45	0.24	4.0	0.28	4	3110712	0.6	45	0.5	12	0.55	4
3110345	0.3	45	0.24	4.5	0.28	4	3110820	0.8	45	0.6	2.0	0.75	4
3110350	0.3	45	0.24	5.0	0.28	4	3110830	0.8	45	0.5	3.0	0.75	4
3110405	0.4	45	0.3	0.5	0.37	4	3110840	0.8	45	0.6	4.0	0.75	4
3110407	0.4	45	0.3	0.75	0.37	4	3110850	0.8	45	0.6	5.0	0.75	4
3110410	0.4	45	0.3	1.0	0.37	4	3110860	0.8	45	0.6	6.0	0.75	4
3110415	0.4	45	0.3	1.5	0.37	4	3110870	0.8	45	0.6	7.0	0.75	4
3110420	0.4	45	0.3	2.0	0.37	4	3110880	0.8	45	0.6	8.0	0.75	4
3110425	0.4	45	0.3	2.5	0.37	4	3110890	0.8	45	0.6	9.0	0.75	4
3110430	0.4	45	0.3	3.0	0.37	4	3110900	0.8	45	0.6	10	0.75	4
3110435	0.4	45	0.3	3.5	0.37	4	3110912	0.8	45	0.5	12	0.75	4
3110440	0.4	45	0.3	4.0	0.37	4	3111025	1.0	45	0.8	2.5	0.95	4
3110445	0.4	45	0.3	4.5	0.37	4	3111030	1.0	45	0.8	3.0	0.95	4
3110450	0.4	45	0.3	5.0	0.37	4	3111040	1.0	45	0.8	4.0	0.95	4
3110455	0.4	45	0.3	5.5	0.37	4	3111050	1.0	45	0.8	5.0	0.95	4
3110460	0.4	45	0.3	6.0	0.37	4	3111060	1.0	45	0.8	6.0	0.95	4
3110510	0.5	45	0.4	1.0	0.45	4	3111070	1.0	45	0.8	7.0	0.95	4
3110515	0.5	45	0.4	1.5	0.45	4	3111080	1.0	45	0.8	8.0	0.95	4
3110520	0.5	45	0.4	2.0	0.45	4	3111090	1.0	45	0.8	9.0	0.95	4
3110525	0.5	45	0.4	2.5	0.45	4	3111100	1.0	45	0.8	10	0.95	4
3110530	0.5	45	0.4	3.0	0.45	4	3111112	1.0	45	0.8	12	0.95	4
3110535	0.5	45	0.4	3.5	0.45	4	3111114	1.0	50	0.8	14	0.95	4
3110540	0.5	45	0.4	4.0	0.45	4	3111116	1.0	50	0.8	16	0.95	4
3110545	0.5	45	0.4	4.5	0.45	4	3111118	1.0	55	0.8	18	0.95	4
3110550	0.5	45	0.4	5.0	0.45	4	3111120	1.0	55	0.8	20	0.95	4
3110555	0.5	45	0.4	5.5	0.45	4	3111240	1.2	45	1.0	4.0	1.15	4

Packed: 1 pc.
Available WXL® coating only.

