



EXOCARB® WXL®

Premium Performance Carbide End Mills with OSG's Proprietary WXL® Coating

List 3790 (Continued)

WXL-LN-EBD, 2 Flute, Regular Length, Long Neck, Ball End, Rib Processing

SPEED FEED P1139-1148	CARBIDE	WXL	REG	30°	SHANK h6
--------------------------	---------	-----	-----	-----	-------------

±5µm Radius Tolerance



EDP Number	Mill Diameter	Overall Length	Length of Cut	Neck Length	Neck Dia.	Shank Diameter
	D	L	Lc	L1	d2	d
3125140	5.0	90	5.0	40	4.85	6
3125145	5.0	100	5.0	45	4.85	6
3125150	5.0	100	5.0	50	4.85	6
3126100	6.0	60	6.0	10	5.85	6
3126120	6.0	70	6.0	20	5.85	6
3126125	6.0	70	6.0	25	5.85	6

Units: mm

EDP Number	Mill Diameter	Overall Length	Length of Cut	Neck Length	Neck Dia.	Shank Diameter
	D	L	Lc	L1	d2	d
3126130	6.0	80	4.8	30	5.85	6
3126135	6.0	80	6.0	35	5.85	6
3126140	6.0	90	4.8	40	5.85	6
3126145	6.0	100	6.0	45	5.85	6
3126150	6.0	120	4.8	50	5.85	6

Packed: 1 pc.
Available WXL® coating only.



OSG's Performance & Savings

Don't require ultra-high performance? Try HY-PRO® CARB - List HP419 or HP419L (p. 984 or 985)
Machining steel over 54 HRC? Try EXOCARB® WXS® - List 4590 (p. 896-898)

List No.	Work Material																
	P					M			K	N		S	H				
	Carbon Steels			Alloy Steels	Die Steels	Stainless Steels			Cast Iron	Aluminum		Nickel Alloy	Titanium	Hardened Steels			
	Low	Med.	High	4140 4340		300	400	17-4 PH		6061 7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
3790	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

good best

