



EXOCARB® WXL®

Premium Performance Carbide End Mills with OSG's Proprietary WXL® Coating

List 3712 (Continued)

WXL-PC-EBD, 2 Flute, Stub Length, Pencil Neck, Ball End

SPEED FEED PT1162-1169	CARBIDE	WXL	STUB	30°	SHANK h6
Radius Tolerance					
0.2 ≤ D ≤ 6			+/-0.005mm		



Units: mm

EDP Number	Mill Diameter	Overall Length	Length of Cut	Minimum Neck Diameter	Effective Neck Length	Neck Taper	Shank Diameter	Type
	D	L	Lc	d1	L1	θn	d	
3170073	0.5	45	0.40	0.48	8.0	0.5°	4	1
3170074	0.5	45	0.40	0.48	10.0	0.5°	4	1
3170081	0.5	45	0.40	0.48	4.0	1.0°	4	1
3170082	0.5	45	0.40	0.48	6.0	1.0°	4	1
3170083	0.5	45	0.40	0.48	8.0	1.0°	4	1
3170084	0.5	45	0.40	0.48	10.0	1.0°	4	1
3170085	0.5	50	0.40	0.48	12.0	1.0°	4	1
3170091	0.6	45	0.50	0.58	2.0	0.5°	4	1
3170092	0.6	45	0.50	0.58	4.0	0.5°	4	1
3170093	0.6	45	0.50	0.58	6.0	0.5°	4	1
3170094	0.6	45	0.50	0.58	8.0	0.5°	4	1
3170095	0.6	45	0.50	0.58	10.0	0.5°	4	1
3170096	0.6	45	0.50	0.58	12.0	0.5°	4	1
3170097	0.6	50	0.50	0.58	16.0	0.5°	4	1
3170101	0.6	45	0.50	0.58	4.0	1.0°	4	1
3170102	0.6	45	0.50	0.58	6.0	1.0°	4	1
3170103	0.6	45	0.50	0.58	8.0	1.0°	4	1
3170104	0.6	45	0.50	0.58	10.0	1.0°	4	1
3170105	0.6	45	0.50	0.58	12.0	1.0°	4	1
3170106	0.6	50	0.50	0.58	16.0	1.0°	4	1
3170111	0.8	45	0.60	0.78	4.0	0.5°	4	1
3170112	0.8	45	0.60	0.78	6.0	0.5°	4	1
3170113	0.8	45	0.60	0.78	8.0	0.5°	4	1
3170114	0.8	45	0.60	0.78	12.0	0.5°	4	1
3170121	0.8	45	0.60	0.78	8.0	1.0°	4	1
3170122	0.8	45	0.60	0.78	12.0	1.0°	4	1
3170123	0.8	50	0.60	0.78	16.0	1.0°	4	1
3170131	1.0	45	0.63	0.95	6.0	0.5°	4	3
3170132	1.0	45	0.63	0.95	8.0	0.5°	4	3
3170133	1.0	45	0.63	0.95	10.0	0.5°	4	3
3170134	1.0	45	0.63	0.95	12.0	0.5°	4	3
3170135	1.0	50	0.63	0.95	16.0	0.5°	4	3
3170136	1.0	55	0.63	0.95	18.0	0.5°	4	3
3170137	1.0	55	0.63	0.95	20.0	0.5°	4	3
3170138	1.0	60	0.63	0.95	25.0	0.5°	4	3
3170139	1.0	65	0.63	0.95	30.0	0.5°	4	3
3170140	1.0	70	0.63	0.95	35.0	0.5°	4	3
3170141	1.0	45	0.63	0.95	10.0	1.0°	4	3
3170142	1.0	50	0.63	0.95	16.0	1.0°	4	3
3170143	1.0	55	0.63	0.95	20.0	1.0°	4	3
3170144	1.0	60	0.63	0.95	25.0	1.0°	4	3
3170145	1.0	65	0.63	0.95	30.0	1.0°	4	3
3170146	1.0	70	0.63	0.95	35.0	1.0°	4	3
3170147	1.0	80	0.63	0.95	40.0	1.0°	4	3
3170148	1.0	90	0.63	0.95	50.0	1.0°	4	3
3170149	1.0	100	0.63	0.95	60.0	1.0°	4	3
3170150	1.0	110	0.63	0.95	70.0	1.0°	4	3
3170151	1.0	45	0.63	0.95	8.0	1.5°	4	3
3170152	1.0	45	0.63	0.95	10.0	1.5°	4	3
3170153	1.0	45	0.63	0.95	12.0	1.5°	4	3

Packed: 1 pc.
Available WXL® coating only.

