



EXOCARB® WXL®

Premium Performance Carbide End Mills with OSG's Proprietary WXL® Coating

List 3712 (Continued)

WXL-PC-EBD, 2 Flute, Stub Length, Pencil Neck, Ball End

SPEED FEED PT162-1169	CARBIDE	WXL	STUB	30°	SHANK h6
Radius Tolerance					
0.2≤D≤6			+/-0.005mm		



Units: mm

EDP Number	Mill Diameter	Overall Length	Length of Cut	Minimum Neck Diameter	Effective Neck Length	Neck Taper	Shank Diameter	Type
	D	L	Lc	d1	L1	θn	d	
3170226	1.5	65	0.95	1.42	30.0	1.0°	4	3
3170227	1.5	70	0.95	1.42	35.0	1.0°	4	3
3170230	1.5	45	0.95	1.42	10.0	1.5°	4	3
3170231	1.5	45	0.95	1.42	12.0	1.5°	4	3
3170232	1.5	55	0.95	1.42	16.0	1.5°	4	3
3170233	1.5	55	0.95	1.42	20.0	1.5°	4	3
3170234	1.5	60	0.95	1.42	25.0	1.5°	4	3
3170235	1.5	65	0.95	1.42	30.0	1.5°	4	3
3170236	1.5	70	0.95	1.42	35.0	1.5°	4	3
3170241	1.5	70	0.95	1.42	38.6	2.0°	4	4
3170271	2.0	45	1.26	1.93	8.0	0.5°	4	3
3170272	2.0	45	1.26	1.93	10.0	0.5°	4	3
3170273	2.0	45	1.26	1.93	12.0	0.5°	4	3
3170274	2.0	50	1.26	1.93	16.0	0.5°	4	3
3170275	2.0	55	1.26	1.93	20.0	0.5°	4	3
3170276	2.0	65	1.26	1.93	26.0	0.5°	4	3
3170277	2.0	70	1.26	1.93	30.0	0.5°	4	3
3170278	2.0	75	1.26	1.93	35.0	0.5°	4	3
3170279	2.0	80	1.26	1.93	40.0	0.5°	4	3
3170281	2.0	50	1.26	1.93	16.0	1.0°	4	3
3170282	2.0	55	1.26	1.93	20.0	1.0°	4	3
3170283	2.0	65	1.26	1.93	25.0	1.0°	4	3
3170284	2.0	70	1.26	1.93	30.0	1.0°	4	3
3170285	2.0	75	1.26	1.93	35.0	1.0°	4	3
3170286	2.0	80	1.26	1.93	40.0	1.0°	4	3
3170287	2.0	90	1.26	1.93	50.0	1.0°	6	3
3170288	2.0	100	1.26	1.93	60.0	1.0°	6	3
3170289	2.0	110	1.26	1.93	70.0	1.0°	6	3
3170291	2.0	50	1.26	1.93	16.0	1.5°	4	3
3170292	2.0	55	1.26	1.93	20.0	1.5°	4	3
3170293	2.0	65	1.26	1.93	25.0	1.5°	4	3
3170294	2.0	70	1.26	1.93	30.0	1.5°	4	3
3170295	2.0	75	1.26	1.93	35.0	1.5°	4	3
3170296	2.0	80	1.26	1.93	41.4	1.5°	4	4
3170301	2.0	70	1.26	1.93	31.5	2.0°	4	4
3170321	3.0	50	2.40	2.95	8.0	0.5°	6	1
3170322	3.0	50	2.40	2.95	10.0	0.5°	6	1
3170323	3.0	55	2.40	2.95	12.0	0.5°	6	1
3170324	3.0	55	2.40	2.95	16.0	0.5°	6	1
3170325	3.0	60	2.40	2.95	20.0	0.5°	6	1
3170326	3.0	65	2.40	2.95	25.0	0.5°	6	1
3170327	3.0	70	2.40	2.95	30.0	0.5°	6	1
3170328	3.0	80	2.40	2.95	35.0	0.5°	6	1
3170329	3.0	85	2.40	2.95	40.0	0.5°	6	1
3170330	3.0	90	2.40	2.95	50.0	0.5°	6	1
3170331	3.0	60	2.40	2.95	20.0	1.0°	6	1
3170332	3.0	65	2.40	2.95	25.0	1.0°	6	1
3170333	3.0	70	2.40	2.95	30.0	1.0°	6	1

Packed: 1 pc.
Available WXL® coating only.

