

EXOCARB® WXL®

Premium Performance Carbide End Mills with OSG's Proprietary WXL® Coating



List 3610

WXL-EBD, 2 Flute, Regular Length, Ball End

NEW SIZES	SPEED FEED P1135	CARBIDE	WXL	REG	30°	SHANK h6
------------------	----------------------------	----------------	------------	------------	------------	--------------------

Radius Tolerance	
1/32 ≤ D ≤ 3/16	+0.0002" / -0.0002"
1/4 ≤ D ≤ 1/2	+0.0001" / -0.0003"



Units: Inch

EDP Number	Mill Diameter	Overall Length	Length of Cut	Shank Diameter
	D	L	Lc	d
36100111	1/32	2-1/2	1/32	1/4
36100211	1/16	2-1/2	1/16	1/4
36100311	3/32	2-1/2	3/32	1/4
36100411	1/8	3	1/8	1/4
36101011	5/32	2-1/2	5/32	1/4

EDP Number	Mill Diameter	Overall Length	Length of Cut	Shank Diameter
	D	L	Lc	d
36100511	3/16	3	3/16	1/4
36100611	1/4	3	1/4	1/4
36100711	5/16	4	5/16	5/16
36100811	3/8	4	3/8	3/8
36100911	1/2	4	1/2	1/2

Packed: 1 pc.
Available WXL® coating only.



OSG's Performance & Savings

Don't require ultra-high performance? Try HY-PRO® CARB - List HP421BN, HP416 or HP413 (p. 980-981, 982 or 986)

Machining steel over 54 HRC? Try EXOCARB® WXS® - List 4410 (p. 884)

Work Material

List No.	P					M			K	N		S	H				
	Carbon Steels			Alloy Steels	Die Steels	Stainless Steels			Cast Iron	Aluminum		Nickel Alloy	Titanium	Hardened Steels			
	Low	Med.	High			300	400	17-4 PH		6061 7075	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
3610	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

good best

