



EXOCARB® WXL®

Premium Performance Carbide End Mills with OSG's Proprietary WXL® Coating

List 3771

WXL-CR-PHS, 4 Flute, Regular Length, Corner Radius

SPEED FEED P1175	CARBIDE	WXL	REG	30°	SHANK h6
---------------------	---------	-----	-----	-----	-------------

Milling Diameter Tolerance	
3 ≤ D ≤ 12	+0 / -0.02mm



Units: mm

EDP Number	Mill Diameter	Corner Radius	Overall Length	Length of Cut	Shank Diameter
	D	R	L	Lc	d
37710000	3	0.2	60	8	6
37710001	3	0.5	60	8	6
37710002	4	0.2	70	11	6
37710003	4	0.5	70	11	6
37710004	4	1.0	70	11	6
37710005	5	0.2	80	13	6
37710006	5	0.5	80	13	6
37710007	5	1.0	80	13	6
37710008	6	0.2	90	13	6
37710009	6	0.5	90	13	6
37710010	6	1.0	90	13	6
37710011	6	1.5	90	13	6
37710012	6	2.0	90	13	6
37710013	8	0.5	100	19	8

EDP Number	Mill Diameter	Corner Radius	Overall Length	Length of Cut	Shank Diameter
	D	R	L	Lc	d
37710014	8	1.0	100	19	8
37710015	8	1.5	100	19	8
37710016	8	2.0	100	19	8
37710017	10	0.5	100	22	10
37710018	10	1.0	100	22	10
37710019	10	1.5	100	22	10
37710020	10	2.0	100	22	10
37710021	10	3.0	100	22	10
37710022	12	0.5	110	26	12
37710023	12	1.0	110	26	12
37710024	12	1.5	110	26	12
37710025	12	2.0	110	26	12
37710026	12	3.0	110	26	12

Packed: 1 pc.
Available WXL® coating only.



OSG's Performance & Savings

Don't require ultra-high performance? Try HY-PRO® CARB - List HP434 or HP435 (p. 987-988 or 990)

Machining steel over 54 HRC? Try EXOCARB® WXS® - List 4571 (p. 889)

Work Material

P		M	K	N	S	H
Carbon Steels		Stainless Steels		Aluminum	Nickel	Hardened Steels
Low	Med					