



List 4592 (Continued)

SPEED FEED P1189	CARBIDE	WXS		STUB	30°	SHANK h6
---------------------	---------	-----	--	------	-----	-------------

WXS-CPR, 2 Flute, Stub Length, Long Neck, Corner Radius, Rib Processing

±5µm Corner Radius Tolerance

Units: mm

EDP Number	Mill Diameter	Corner Radius	Overall Length	Length of Cut	Neck Length	Neck Diameter	Shank Diameter
	D	R	L	Lc	L1	d2	d
3103006	3.0	0.20	70	2.50	30	2.85	6
3103007	3.0	0.20	80	2.50	35	2.85	6
3103008	3.0	0.30	60	2.50	12	2.85	6
3103009	3.0	0.30	60	2.50	16	2.85	6
3103010	3.0	0.30	70	2.50	20	2.85	6
3103011	3.0	0.30	70	2.50	25	2.85	6
3103012	3.0	0.30	70	2.50	30	2.85	6
3103013	3.0	0.30	80	2.50	35	2.85	6
3103014	3.0	0.50	60	2.50	12	2.85	6
3103015	3.0	0.50	60	2.50	16	2.85	6
3103016	3.0	0.50	70	2.50	20	2.85	6
3103017	3.0	0.50	70	2.50	25	2.85	6
3103018	3.0	0.50	70	2.50	30	2.85	6
3103019	3.0	0.50	80	2.50	35	2.85	6

Packed: 1 pc.
Available WXS® coating only.



OSG's Performance & Savings

Want to turbo-charge performance? Try EXOPRO® PHX - List 9592 (p. 846)

List No.	Work Material																
	P					M			K	N		S	H				
	Carbon Steels			Alloy Steels	Die Steels	Stainless Steels			Cast Iron	Aluminum		Nickel Alloy	Titanium	Hardened Steels			
	Low	Med.	High	4140		300	400	17-4 PH		6061	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
4592	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>					<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	

good best

