

EXOCARB® WXS®



Ultra Premium Performance Carbide End Mills with OSG's Proprietary WXS® Coating

List 4430 WHILE SUPPLIES LAST

WXS-EBM, True 4 Flute, Regular Length, Ball End

SPEED FEED P1193	CARBIDE	WXS	REG	30°	SHANK h6
Radius Tolerance					
1/4 ≤ D ≤ 1/2			± 0.0006"		



EDP Number	Mill Diameter	Overall Length	Length of Cut	Shank Diameter
	D	L	Lc	d
44301111	1/4	3-1/2	1/2	1/4
44301311	5/16	4	5/8	5/16

Units: Inch

EDP Number	Mill Diameter	Overall Length	Length of Cut	Shank Diameter
	D	L	Lc	d
44301411	3/8	4	3/4	3/8
44301611	1/2	4-3/8	7/8	1/2

Packed: 1 pc.
Available WXS® coating only.



OSG's Performance & Savings

Don't require ultra-high performance? Try HY-PRO® CARB - List HP441BN (p. 980-981)

List No.	Work Material																
	P					M			K	N		S		H			
	Carbon Steels			Alloy Steels	Die Steels	Stainless Steels			Cast Iron	Aluminum		Nickel Alloy	Titanium	Hardened Steels			
	Low	Med.	High			300	400	17-4 PH		6061	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
4430	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>				<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	

good best

