



## List 4472

WXS-CRE, 5 Flute, Stub Length, **High Feed**, Corner Radius

<b>SPEED FEED</b>	<b>CARBIDE</b>	<b>WXS</b>	<b>STUB</b>	<b>SHANK</b>
P1187				h6

Milling Diameter Tolerance	
1/8 ≤ D ≤ 3/16	+0 / -0.0008"
1/4 ≤ D ≤ 1/2	+0 / -0.0012"



Units: Inch

EDP Number	Mill Diameter	Corner Radius	Overall Length	Length of Cut	Neck Length	Neck Diameter	Shank Diameter
	D	R	L	Lc	L1	d2	d
447200013	1/8	1/32	2-1/4	0.062	0.375	0.113	1/4
447200113	3/16	1/16	2-1/4	0.094	0.562	0.168	1/4
447200213	1/4	1/16	3	0.098	1.000	0.226	1/4
447200313	5/16	3/32	3	0.129	1.250	0.280	5/16
447200413	3/8	3/32	4	0.149	1.500	0.336	3/8
447200513	1/2	1/8	5	0.200	2.000	0.460	1/2

Packed: 1 pc.  
Available WXS® coating only.



List No.	Work Material																
	P					M			K	N		S		H			
	Carbon Steels			Alloy Steels	Die Steels	Stainless Steels			Cast Iron	Aluminum		Nickel Alloy	Titanium	Hardened Steels			
	Low	Med.	High	4140		300	400	17-4 PH			6061	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC
4472	1010	1035	1065	4340		<input type="checkbox"/>	<input type="checkbox"/>		<input type="checkbox"/>	7075				<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

good  best

