



EXOCARB® WXS®

Ultra Premium Performance Carbide End Mills with OSG's Proprietary WXS® Coating

List 4572

WXS-CRE, Multiple Flute, Stub Length, High Feed, Corner Radius

SPEED FEED P1188	CARBIDE	WXS	STUB	SHANK h6
---------------------	---------	-----	------	-------------

Milling Diameter Tolerance	
2≤D≤12	+0 / -0.03mm



Units: mm

EDP Number	Mill Diameter	Corner Radius	Overall Length	Length of Cut	Neck Length	Neck Diameter	Shank Diameter	Number of Flutes
	D	R	L	Lc	L1	d2	d	
48106421	2	0.50	50	0.8	8.0	2.0	6	4
48106433	3	0.75	55	1.2	12.0	2.7	6	5
48106445	4	1.00	55	1.6	12.0	3.6	6	5
48106467	6	1.50	90	2.5	12.0	5.4	6	5
48106489	8	2.00	100	3.5	16.0	7.2	8	5
48106509	10	2.00	100	4.0	20.0	9.0	10	5
48106533	12	3.00	110	5.0	24.0	11.0	12	5

Packed: 1 pc.
Available WXS® coating only.



Work Material

List No.	P					M			K	N		S		H			
	Carbon Steels			Alloy Steels	Die Steels	Stainless Steels			Cast Iron	Aluminum		Nickel Alloy	Titanium	Hardened Steels			
	Low 1010 1018	Med. 1035 1045	High 1065	4140 4340	300	400	17-4 PH	6061 7075		Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
4572	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	

good best

