



OIL ONLY CAB MOUNT SPILL KIT

CAB-O



Spill kit | Oil only | Cab Mount

Absorbency: 9.19 US Gallons | 34.8 Liters of oil**

Base Fiber: Polypropylene

| Product Code | Color | Format | Size inches(cm) | Recycled Content | Units/Case | LTL/Pallet | FTL/Pallet |
|--------------|-------|-----------|-----------------|------------------|------------|------------|------------|
| CAB-O | Black | Spill kit | 28" X 13" X 11" | 0% | 1 | 24 | 24 |

CAB MOUNT SPILL KIT

This spill kit is designed to be affixed to the outside of a transport vehicle for use in emergency situations. The kit features a combination of pads and socks that will contain and recover up to 9.19 US Gallons of Oil along with the basic equipment needed to handle the clean up process. **Spill kit's contents include:**



15 x Pads
size 15" x 18"

The pads in this spill kit are Oil only meltblown sonic bonded polypropylene and will absorb just oil-based fluids.

1 Bag Granular

A 3 lb bag of Granular to assist in the final clean up stage

1 pair of gloves

Waterproof gloves help to ensure safe handling of spilled substance.



2 x Socks
size 3" x 4"

Oil only socks are made with a strong spun-bond outer sleeve and a recycled meltblown polypropylene and cellulose core, producing a resilient no-lint product.



1 x Drain Cover
size 36" x 36"

This Neoprene Drain Cover is 1/16th thick and ideal for covering close by man holes or drains that may be in danger of the spill present.



2 x Waste Bag

These are made from a tough grade of polythene. There is also a cable tie supplied so that the waste can be secured safely.

Compliance

| Related Regulations | Description |
|----------------------------|---|
| 29 CFR 1910.120(j)(1)(vii) | ...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur. |
| 29 CFR 1910.120(j)(1)(vii) | U.S. Department of Transportation specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur. |
| 29 CFR 1910.22(a)(2) | The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition. |
| 40 CFR 263.31 | Transporters "must clean up any hazardous waste discharge that occurs during transportation. |

Evolution Sorbent Products LLC

PDS Date: April, 2016 © Evolution Sorbent Products LLC

| Email: orderdesk@espsorbents.ca | Visit: ca.espsorbents.com

- * Basis weights and recycled content are ± 5%
- ** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water.

Statistical average derived from real time production QC data.