



340 Litre (90 Gallon) Dash Bin Oil only Spill Kit

DASH-O90

Spill kit | 340 Litre | Oil only | Dash bin

Absorbency: 340 Litres | 90 US Gallons of oil*

Base Fibre: Cellulose and polypropylene



340 Litre (90 US Gallon) Dash Bin

This spill kit is contained in a highly portable wheeled bin with a hinged lid that is ideal for locations where a quantity of sorbents need to be taken to the site of a spill at a moments notice. The wheels are made from tough rubber and cannot puncture.

Spill kit's contents include:



150 x Pads
size 40 cm x 46 cm (16" x 18")



20 x Socks
size 8 cm x 1.2 m (3" x 4')



8 x Pillows
size 23 cm x 38 cm



10 x Waste Bags

These Oil only pads are very absorbent 240 gsm weight Coldform2™ made from recycled and renewable sourced natural fibres. They have a spun-bond lamination added for extra strength.

Oil only socks are made with a strong spun-bond outer sleeve and a recycled meltblown polypropylene and cellulose core, producing a resilient no-lint product.

These Oil only pillows are made from a spun-bond outer casing that is both stitched and heat sealed to enclose a recycled polypropylene core. The surface is fast-wicking so promotes faster absorption.

These are made from a tough grade of polythene. There is also a cable tie supplied so that the waste can be secured safely.

2 pairs of gloves

Waterproof gloves help to ensure safe handling of spilled substance.

2 pairs of goggles

All-in one clear goggles provide eye protection from splashes.

1 guide book

An informative booklet that advises on spill recovery.

* Basis weights and recycled content are $\pm 5\%$

** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

*** Weight per case ± 0.5 kg/lbs.

Compliance

Related Regulations	Description
29 CFR 1910.120(j)(1)(vii)	...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.120(j)(1)(vii)	U.S. Department of Transportation specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.22(a)(2)	The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition.
40 CFR 263.31	Transporters "must clean up any hazardous waste discharge that occurs during transportation.