



113 Litre (30 Gallon) Dash Bin Maintenance Spill Kit

DASH-U30

Spill kit | 113 Litre | Maintenance | Dash bin

Absorbency: 113 Litres | 30 US Gallons**


Base Fibre: Cellulose



113 Litre (30 US Gallon) Dash Bin

This spill kit is contained in a highly portable wheeled bin with a hinged lid that is ideal for locations where a quantity of sorbents need to be taken to the site of a spill at a moments notice. The wheels are made from tough rubber and cannot puncture.

Spill kit's contents include:



40 x Pads
size 40 cm x 46 cm (16" x 18")

The pads in this spill kit are medium weight Coldform2™ and feature recycled and renewable sourced natural fibres. A spun-bond lamination is added for extra strength. These pads will recover both oil and water-based fluids.



3 x Socks
size 8 cm x 1.2 m (3" x 4')

These socks feature a spun-bond outer sleeve with a durable stitched seam. This tube is then filled with a next generation super absorbent flake core and sealed with a durable metal clip.



4 x Pillows
size 23 cm x 38 cm

These pillows feature a spun-bond outer casing and a super absorbent flake core. The core is a next generation absorbent that will absorb and retain both oil-based and water-based fluids.



4 x Waste Bag

These are made from a tough grade of polythene. A cable tie is also supplied so that the waste can be secured safely.

1 pair of gloves

Waterproof gloves help to ensure safe handling of spilled substance.

1 pair of goggles

All-in one clear goggles provide eye protection from splashes.

Compliance

Related Regulations	Description
29 CFR 1910.120(j)(1)(vii)	...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.120(j)(1)(viii)	U.S. Department of Transportation specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.22(a)(2)	The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition.
40 CFR 263.31	Transporters "must clean up any hazardous waste discharge that occurs during transportation.

* Basis weights and recycled content are $\pm 5\%$

** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

*** Weight per case ± 0.5 kg/lbs.