



20 Litre (5 gallon) Portable Bucket Chemical Spill Kit

SK-Y05P

Spill kit | 20 Litre | Chemical | Plastic bucket

Absorbency: 20 Litres | 5 US Gallons**

Base Fibre: Polypropylene



20 Litre (5 US Gallon) Bucket


The drum container for this spill kit keeps the absorbents clean, dry and ready for use when needed. A clip top lid and a metal handle make for easy portability and quick deployment. Great for indoor or outdoor use and also to add extra support to larger spill kits.

This spill kits feature a combination of pads and socks that will contain and recover a 20 litre spill of hazardous oil-based and water-based fluid as well as the essential equipment needed to handle the clean up process. Please note extra caution should be taken when dealing with hazardous or unknown spill types.

Notes


- Refill 10 pad packs are available for this kit.
- Ensure that disposal of these used sorbents complies with all regulations.

Spill kit's contents include:



10 x Pads
size 38 cm x 46 cm (15" x 18")

The pads in this spill kit are medium weight sonic bonded meltblown polypropylene Chemical. They feature excellent wicking properties and sonic bond points that prevent stray fibres from becoming detached.



3 x Socks
size 8 cm x 1.2 m (3" x 4')

These socks feature a spun-bond outer sleeve with a durable stitched seam. The core is a next generation absorbent that will recover aggressive and unknown spills. Durable plastic clips seal the sock at both ends.



1 x Waste Bag

These are made from a tough grade of polythene. There is also a cable tie supplied so that the waste can be secured safely.



1 pair of gloves

Waterproof gloves help to ensure safe handling of spilled substance.



1 pair of goggles

All-in one clear goggles provide eye protection from splashes.

* Basis weights and recycled content are $\pm 5\%$

** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

*** Weight per case ± 0.5 kg/lbs.

Compliance

Related Regulations	Description
29 CFR 1910.120(j)(1)(vii)	...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.120(j)(1)(vii)	U.S. Department of Transportation specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.22(a)(2)	The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition.
40 CFR 263.31	Transporters "must clean up any hazardous waste discharge that occurs during transportation.