



246 Litre (65 Gallon) Static Overpack Chemical Spill Kit

SK-Y65

Spill kit | 246 Litre | Chemical | Static Overpack

Absorbency: 246 Litres | 65 US Gallons**

Base Fibre: Polypropylene



246 Litre (65 US Gallon) Static Overpack

The drum container for this spill kit keeps the absorbents clean, dry and ready for use when needed. A large gauge threaded lid and rigid construction allows the drum to be used as an overpack.


This spill kits feature a combination of pads, socks and pillows that will contain and recover a 246 litre spill of hazardous oil-based or

water-based fluid as well as the essential equipment needed to handle the clean up process. Please note extra caution should be taken when dealing with hazardous or unknown spill types.

Notes

- Refill 10 pad packs are available for this kit.
- Ensure that disposal of these used sorbents complies with all regulations.

Spill kit's contents include:



100 x Pads

size 38 cm x 46 cm (15" x 18")

The pads in this spill kit are medium weight sonic bonded meltblown polypropylene. Chemical. They feature excellent wicking properties and sonic bond points that prevent stray fibres from becoming detached.



10 x Socks

size 8 cm x 1.2 m (3" x 4')

These socks feature a spun-bond outer sleeve with a durable stitched seam. The core is a next generation absorbent that will recover aggressive and unknown spills. Durable plastic clips seal the sock at both ends.



8 x Pillows

size 23 cm x 38 cm (9" x 15")

These pillows feature a spun-bond outer surface with a super absorbent flake core. This next generation absorbent will absorb and hold large quantities of aggressive, hazardous or unknown fluids.



10 x Waste Bags

These are made from a tough grade of polythene. There is also a cable tie supplied so that the waste can be secured safely.

2 pairs of gloves

Waterproof gloves help to ensure safe handling of spilled substance.

2 pairs of goggles

All-in one clear goggles provide eye protection from splashes.

Compliance

Related Regulations	Description
29 CFR 1910.120(j)(1)(vii)	...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.120(j)(1)(vii)	U.S. Department of Transportation specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.22(a)(2)	The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition.
40 CFR 263.31	Transporters "must clean up any hazardous waste discharge that occurs during transportation.

* Basis weights and recycled content are $\pm 5\%$

** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

*** Weight per case ± 0.5 kg/lbs.